Omniduct Documentation

Release v1.1.19

Matthew Wardrop

May 09, 2022

Contents

1	Supported protocols	1
2	Installation	3
3	Quickstart3.1Task 1: Create a Presto client that connects direct to the database service3.2Task 2: Create a Presto client that connects via ssh to a remote server3.3Task 3: Persist service configuration for use in multiple sessions	5 5 6 7
4	Deployment	9
5	API & IPython Magics5.1Core Classes5.2Databases5.3Filesystems5.4Remotes5.5Caches5.6Registry Management	11 15 90 118 144 156
6	Extensions and Plug-ins	161
7	Contributions	163
8	Indices and tables	165
Ру	thon Module Index	167
In	dex	169

Supported protocols

The currently supported protocols are listed below. The string inside the square brackets after the protocol name (if present) indicates that support for this protocol requires external packages which are not hard-dependencies of *om-niduct*. To install them with omniduct, simply add these strings to the list of desired extras as indicated in *Installation*.

- Databases
 - Druid [druid]
 - HiveServer2 [hiveserver2]
 - Neo4j (experimental)
 - Presto [presto]
 - PySpark [pyspark]
 - Any SQL database supported by SQL Alchemy (e.g. MySQL, Postgres, Oracle, etc) [sqlalchemy]
- Filesystems
 - HDFS [webhdfs]
 - S3 [s3]
 - Local filesystem
- Remotes (also act as filesystems)
 - SSH servers, via CLI backend [ssh] or via Paramiko backend [ssh_paramiko]
- REST Services (generic interface)

Adding support for new protocols is straightforward. If your favourite protocol is missing, feel free to contact us for help writing a patch to support it.

Within each class of protocol (database, filesystem, etc), a certain subset of functionality is guaranteed to be consistent across protocols, making them largely interchangeable programmatically. The common API for each protocol class is documented in the *API & IPython Magics* section, along with any exceptions, caveats and extensions for each implementation.

Installation

If your company/organisation has provided a package that wraps around *omniduct* to provide a library of services, then a direct installation of *omniduct* is not required. Otherwise, you can install it using the standard Python package manager: *pip*. If you use Python 3, you may need to change *pip* references to *pip3*, depending on your system configuration.

pip install omniduct[<comma separated list of protocols>]

For example, if you want access to Presto and HiveServer2, you can run:

pip install omniduct[presto,hiveserver2]

Omitting the list of protocols (i.e. *pip install omniduct*) will mean that the external dependencies required to interface with the protocols indicated in *Supported protocols* will not be automatically installed. Attempts to use these protocols will throw an error with instructions as to which additional dependencies you will need to install.

To install omniduct and all possible dependencies, you can install omniduct using:

pip install omniduct[all]

This is only recommended for casual use, as dragging in unneeded dependencies could lead to complications with other packages on your machine (and is otherwise just generally messy!).

Quickstart

omniduct is designed to be intuitive and uniform in its APIs. As such, insofar as possible, all *Duct* subclasses have a reasonable default configuration, making it possible to quickly create working connections to remote services. Depending on the complexity of your service configuration, it may or may not make sense to use *omniduct*'s registry utilities, and so this quickstart will show you how to directly create *Duct* instances, as well as how to work with a *Duct* registry. Though we only use *PrestoClient* explicitly in the following, since all *Duct* instances have the same basic API, the same methodology will work with all *Duct* subclasses.

If you are looking deploy *omniduct* into production or as part of a company specific package, or want to share your service configuration with others, you will likely also be interested in *Deployment*.

3.1 Task 1: Create a Presto client that connects direct to the database service

Method 1: Via PrestoClient class

(continues on next page)

(continued from previous page)

```
presto_local: Query: Complete after 1.20 sec on 2017-10-13.
_col0
0 42
```

Method 2: Via Duct subclass registry

```
>>> from omniduct import Duct
>>> pc = Duct.for_protocol('presto')(host='<host>', port=8080)
>>> pc.query("SELECT 42")
# ... And all of the rest from above.
```

Method 3: Via DuctRegistry

```
>>> from omniduct import DuctRegistry
>>> duct_registry = DuctRegistry()
>>> pc = duct_registry.new(name='presto_local', protocol='presto',
                           host='localhost', port=8080, register_magics=True)
. . .
>>> # Or: pc = duct_registry['presto_local']
>>> # Or: pc = duct_registry.get_proxy(by_kind=True).databases.presto_local
>>> pc.query("SELECT 42")
presto_local: Query: Complete after 0.14 sec on 2017-10-13.
   _col0
0
     42
# The following assumes that you are using an IPython/Jupyter console
>>> %%presto_local
... {# magics are created and queries rendered using Jinja2 templating #}
... SELECT {{ 4 * 10 + 2 }}
. . .
presto_local: Query: Complete after 1.20 sec on 2017-10-13.
   _col0
0
      42
```

3.2 Task 2: Create a Presto client that connects via ssh to a remote server

Method 1: Directly passing 'RemoteClient' instance to PrestoClient constructor

(continues on next page)

(continued from previous page)

```
PrestoClient: Query: Complete after 0.14 sec on 2017-10-13.
__col0
0 42
```

Method 2: Passing name of 'RemoteClient' instance via Registry

```
>>> from omniduct import DuctRegistry
>>> duct_registry = DuctRegistry()
>>> duct_registry.new('my_server', protocol='ssh', host='<remote_host>', port=22)
<omniduct.remotes.ssh.SSHClient at 0x110bab550>
>>> duct_registry.new('presto_remote', protocol='presto', remote='my_server',
                      host='<host_relative_to_remote>', port=8080)
<omniduct.databases.presto.PrestoClient at 0x110c04a58>
# Query sent to port-forwarded remote service
>>> %%presto_remote
... SELECT 42
. . .
presto_remote: Query: Connecting: Connected to localhost:8080 on <remote_host>.
presto_remote: Query: Complete after 7.30 sec on 2017-10-13.
   col0
0
      42
```

3.3 Task 3: Persist service configuration for use in multiple sessions

```
>>> from omniduct import DuctRegistry
>>> duct_registry = DuctRegistry()
# Specify a YAML configuration verbatim (or the filename of a yaml configuration)
# In this case we create the configuration for the previous task.
>>> duct_registry.register_from_config("""
... remotes:
... my_server:
. . .
          protocol: ssh
           host: <remote_host>
. . .
... databases:
... presto_local:
          protocol: presto
. . .
           host: <host_relative_to_remote>
. . .
          port: 8080
• • •
           remote: my_server
. . .
... """)
>>> %%presto_local
... SELECT 42
. . .
# And so on.
```

Method 1: Manually import configuration into 'DuctRegistry'

Method 2: Save configuration to '~/.omniduct/config', and autoload

Assuming that the above YAML file has been saved to ~/.omniduct/config, or to a file located at the location pointed to by the OMNIDUCT_CONFIG environment variable, you can directly restore your configuration by importing from omniduct.session.

```
>>> from omniduct.session import *
>>> presto_local
<omniduct.databases.presto.PrestoClient at 0x110c04a58>
>>> %%presto_local
... SELECT 42
# And so on.
```

Deployment

While Omniduct can be used on its own by manually constructing the services that you need as part of your scripts and packages, it was designed specifically to integrate well into a organisation-specific Python wrapper package that preconfigures the services available within that organisation environment. Typically such deployments would take advantage of Omniduct's *DuctRegistry* to conveniently expose services within such a package.

An example wrapper package is provided alongside the omniduct module to help bootstrap your own wrappers.

If you need any assistance, please do not hesitate to reach out to us via the GitHub issue tracker.

API & IPython Magics

5.1 Core Classes

All protocol implementations are subclasses (directly or indirectly) of *Duct*. This base class manages the basic lifecycle, connection management and protocol registration. When a subclass of *Duct* is loaded into memory, and has at least one protocol name in the *PROTOCOLS* attribute, then *Duct* registers that class into its subclass registry. This class can then be conveniently accessed by: *Duct.for_protocol('<protocol_name>')*. This empowers the accompanying registry tooling bundled with omniduct, as documented in *Registry Management*.

Protocol implementations may also (directly or indirectly) be subclasses of *MagicsProvider*, which provides a common API to registry IPython magics into the user's session. If implemented, the accompanying registry tooling can automatically register these magics, as documented in *Registry Management*.

5.1.1 Duct

Bases: object

The abstract base class for all protocol implementations.

This class defines the basic lifecycle of service connections, along with some magic that provides automatic registration of Duct protocol implementations. All connections made by *Duct* instances are lazy, meaning that instantiation is "free", and no protocol connections are made until required by subsequent interactions (i.e. when the value of any attribute in the list of *connection_fields* is accessed). All *Ducts* will automatically connnect and disconnect as required, and so manual intervention is not typically required to maintain connections.

Attributes

- protocol (str) The name of the protocol for which this instance was created (especially useful if a Duct subclass supports multiple protocols).
- **name** (*str*) The name given to this *Duct* instance (defaults to class name).

- **host** (*str*) The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._*host* to see remote host).
- **port** (*int*) The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._*port*).
- username (*str*, *bool*) The username to use for the service.
- **password** (*str*, *bool*) The password to use for the service.
- **registry** (*None, omniduct.registry.DuctRegistry*) A reference to a *DuctRegistry* instance for runtime lookup of other services.
- remote (None, omniduct.remotes.base.RemoteClient) A reference to a RemoteClient instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache) A reference to a Cache instance to add support for caching, if applicable.
- **connection_fields** (*tuple<str>*, *list<str>*) A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- **prepared_fields** (*tuple<str>*, *list<str>*) A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.
- · Additional attributes including 'host', 'port', 'username' and 'password' are
- documented inline.
- · Class Attributes -
 - AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
 - **DUCT_TYPE** (**Duct.Type**): The type of *Duct* service that is provided by this Duct instance. Should be overridden by subclasses as appropriate.
 - **PROTOCOLS** (list<str>): The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (protocol=None, name=None, registry=None, remote=None, host=None, port=None, username=None, password=None, cache=None, cache_namespace=None)

- protocol (str, None): Name of protocol (used by Duct registries to inform Duct instances of how they were instantiated).
- name (str, None): The name to used by the Duct instance (defaults to class name if not specified).
- **registry** (DuctRegistry, None): The registry to use to lookup remote and/or cache instance specified by name.

remote (str, RemoteClient): The remote by which the ducted service should be contacted.

host (str): The hostname of the service to be used by this client. port (int): The port of the service to be used by this client. username (str, bool, None): The username to authenticate with if necessary.

If True, then users will be prompted at runtime for credentials.

- **password (str, bool, None): The password to authenticate with if necessary.** If True, then users will be prompted at runtime for credentials.
- cache(Cache, None): The cache client to be attached to this instance. Cache will only used by specific methods as configured by the client.

cache_namespace(str, None): The namespace to use by default when writing to the cache.

classmethod for_protocol(protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures *self.registry*, *self.remote* and *self.cache* values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

_prepare()

This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct_host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = <port>.

Type int

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to duct.disconnect().connect().

Returns A reference to this object.

Return type Duct instance

5.1.2 MagicsProvider

class omniduct.utils.magics.MagicsProvider Bases: object

5.2 Databases

All database clients are expected to be subclasses of *DatabaseClient*, and so will share a common API and inherit a suite of IPython magics. Protocol implementations are also free to add extra methods, which are documented in the "Subclass Reference" section below.

5.2.1 Common API

An abstract class providing the common API for all database clients.

Note: *DatabaseClient* subclasses are callable, so that one can use *DatabaseClient(...)* as a short-hand for *DatabaseClient.query(...)*.

Class Attributes

- DUCT_TYPE (Duct.Type) The type of Duct protocol implemented by this class.
- DEFAULT_PORT (int) The default port for the database service (defined by subclasses).
- CURSOR_FORMATTERS (dict<str, CursorFormatter) asdsd
- **DEFAULT_CURSOR_FORMATTER** (*str*) ...

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

- __init___(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)
 - **session_properties (dict): A mapping of default session properties** to values. Interpretation is left up to implementations.
 - **templates (dict): A dictionary of name to template mappings. Additional** templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (bool) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

```
execute (statement, wait=True, cursor=None, session_properties=None, **kwargs) Execute a statement against this database and return a cursor object.
```

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- ****kwargs** (*dict*) Extra keyword arguments to be passed on to _*execute*, as implemented by subclasses.
- **template** (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (*bool*) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

stream(statement, format=None, format_opts={}, batch=None, **kwargs)
Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

query_from_file (file, fs=None, **kwargs)

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

template_names

A list of names associated with the templates associated with this client.

Type list

template_add(name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as *jinja2* templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type *PrestoClient*

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError - If name is not associated with a template.

Returns The requested template.

Return type str

template_variables (*name_or_statement*, *by_name=False*) Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

template_render(name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False)

Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

execute_from_template (*name*, *context=None*, ***kwargs*) Render and then execute a named template.

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (*str*) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .query().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (statement, table, if_exists='fail', **kwargs)

Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client_query_to_table*.

Returns The cursor object associated with the execution.

Return type DB-API cursor

dataframe_to_table (df, table, if_exists='fail', **kwargs)

Upload a local pandas dataframe into a table in this database.

Parameters

- **df** (pandas.DataFrame) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client._dataframe_to_table*.

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

• **namespace** (*str*) – The namespace in which to look for tables.

- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_exists (table, renew=True, **kwargs)

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_drop (table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_desc(table, renew=True, **kwargs)

Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_partition_cols(table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_head (table, n=10, renew=True, **kwargs)

Retrieve the first n rows from a table.

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

- **table** (*str*) The table from which to extract data.
- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

- **DatabaseClient Quirks:** This method may be overridden by subclasses, but provides the following default behaviour:
 - Ensures *self.registry*, *self.remote* and *self.cache* values are instances of the right types.
 - It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
 - It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
 - Ensures value of self.port is an integer (or None).

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%*hive*: For querying the database.
- %%hive.execute: For executing a statement against the database.
- %%hive.stream: For executing a statement against the database, and streaming the results.
- %%hive.template: The defining a new template.
- %%hive.render: Render a provided query statement.
- Line Magics:
 - %*hive*: For querying the database using a named template.
 - %hive.execute: For executing a named template statement against the database.
 - %hive.stream: For executing a named template against the database, and streaming the results.
 - %hive.render: Render a provided a named template.
 - %hive.desc: Describe the table nominated.
 - %hive.head: Return the first rows in a specified table.
 - %*hive.props*: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

5.2.2 IPython Magics

While it is possible in an IPython/Jupter notebook session to write code along the lines of:

```
results = db_client.query("""
SELECT *
FROM table
WHERE condition = 1
""", format='pandas', ...)
```

manually encapsulating queries in quotes quickly becomes tiresome and cluttered. We therefore expose most functionality as IPython magic functions. For example, the above code could instad be rendered (assuming magic functions have been registered under the name *db_client*):

```
%%db_client results format='pandas' ...
SELECT *
FROM table
WHERE condition = 1
```

Especially when combined with templating, this can greatly improve the readability of your code.

In the following, all of the provided magic functions are listed along with the equivalent programmatic code. Note that all arguments are passed in as space-separated tokens after the magic's name. Position-arguments are always interpreted as strings and keyword arguments are expected to be provided in the form '<key>=<value>', where the <value> will be run as Python code and the resulting value passed on to the underlying function/method as:

db_client.method(..., key=eval('<value>'), ...)

Where present in the following, arguments in square brackets after the magic name are the options specific to the magic function, and an ellipsis ('...') indicates that any additional keyword arguments will be passed on to the appropriate method.

Querying

```
%%<name> [variable=None show='head' transpose=False ...]
SELECT *
FROM table
WHERE condition = 1
```

This magic is equivalent to calling db_client.query("<sql>", ...), with the following magic-specific parameters offering additional flexibility:

- variable (str): The name of the local variable where the output should be stored (typically not referenced directly by name)
- **show** (**str, int, None**): What should be shown if variable is specified (if not the entire output is returned). Allowed values are 'all', 'head' (first 5 rows), 'none', or an integer which specifies the number of rows to be shown.
- **transpose (bool):** If format is pandas, whether the shown results, as defined above, should be transposed. Data stored into variable is never transposed.

There is also a line-magic version if you are querying using an existing template:

results = %<name> variable='<template_name>' ...

which is equivalent to db_client.query_from_template('<template_name>', context=locals()). Note that one would typically pass this the template name as a position argument, i.e. %<name> <template_name>.

Executing

```
%%<name>.execute [variable=None ...]
INSERT INTO database.table (field1, field2) VALUES (1, 2);
```

This magic is equivalent to db_client.execute('<sql>', ...), with the *variable* argument functioning as previously for the query magic.

As for the query magic, there is also a template version:

Streaming

```
%%<name>.stream [variable=None ...]
SELECT *
FROM table
WHERE condition = 1
```

This magic is equivalent to db_client.stream('<sql>', ...), with the *variable* argument functioning as previously for the query magic. Keep in mind that the value returned from this method is a generator object.

As for the query magic, there is also a template version:

Templating

To create a new template:

```
%%<name>.template <template_name>
SELECT *
FROM table
WHERE condition = 1
```

which is equivalent to db_client.add_template("<template_name>", "<sql>").

You can render a template in the cell body using current context (or specified context):

```
%%<name>.render [context=None, show=True]
SELECT 1 FROM test
```

or if the template has already been created, you can render it directly by name:

%<name>.render [name=None, context=None, show=True]

In both cases, the *context* and *show* parameters respectively control the context from which template variables are extracted and whether the rendered template should be shown (printed to screen) or returned as a string.

Table properties

todo Resolve what to keep and dump here.

```
%%<name>.desc
SELECT 1 FROM test
```

```
%%<name>.head
SELECT 1 FROM test
```

%%<name>.props

5.2.3 Subclass Reference

For comprehensive documentation on any particular subclass, please refer to one of the below documents.

DruidClient

This Duct connects to a Druid server using the *pydruid* python library.

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)

session_properties (dict): A mapping of default session properties to values. Interpretation is left up to implementations.

templates (dict): A dictionary of name to template mappings. Additional templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

```
dataframe_to_table (df, table, if_exists='fail', **kwargs)
```

Upload a local pandas dataframe into a table in this database.

Parameters

- df (pandas.DataFrame) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client._dataframe_to_table*.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

```
execute (statement, wait=True, cursor=None, session_properties=None, **kwargs) Execute a statement against this database and return a cursor object.
```

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- **kwargs (dict) Extra keyword arguments to be passed on to _execute, as implemented by subclasses.
- template (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (*bool*) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_file(file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template(name, context=None, **kwargs)

Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol(protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = <port>.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

DruidClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.

- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

query_from_file (file, fs=None, **kwargs)

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (dict) Extra keyword arguments to pass on to DatabaseClient.query.

Returns The results of the query formatted as nominated.

Return type object

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (str) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*query*().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (statement, table, if_exists='fail', **kwargs)

Run a query and store the results in a table in this database.

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.

- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client_query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type Duct instance

register_magics (base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%*hive*: For querying the database.
- %%*hive.execute*: For executing a statement against the database.
- %%hive.stream: For executing a statement against the database, and streaming the results.
- %%hive.template: The defining a new template.
- %%hive.render: Render a provided query statement.

• Line Magics:

- %*hive*: For querying the database using a named template.
- %hive.execute: For executing a named template statement against the database.
- *%hive.stream*: For executing a named template against the database, and streaming the results.
- %hive.render: Render a provided a named template.
- %hive.desc: Describe the table nominated.
- %hive.head: Return the first rows in a specified table.
- %*hive.props*: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

session_properties

The default session properties used in statement executions.

Type dict
classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

Parameters

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (bool) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream(statement, format=None, format_opts={}, batch=None, **kwargs)

Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

• **statement** (*str*) – The statement to be executed against the database.

- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc (*table*, *renew=True*, ***kwargs*) Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop (table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_exists (table, renew=True, **kwargs)

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head(table, n=10, renew=True, **kwargs)

Retrieve the first *n* rows from a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols (table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add(name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as *jinja2* templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type PrestoClient

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError – If *name* is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (name_or_statement, by_name=False)

Return the set of undeclared variables required for this template.

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '<*username*>'.

Type str

HiveServer2Client

This Duct connects to an Apache HiveServer2 server instance using the *pyhive* or *impyla* libraries.

Attributes

- schema (*str*, *None*) The default schema to use for queries (will default to server-default if not specified).
- **driver** (*str*) One of 'pyhive' (default) or 'impyla', which specifies how the client communicates with Hive.
- **auth_mechanism** (*str*) The authorisation protocol to use for connections. Defaults to 'NOSASL'. Authorisation methods differ between drivers. Please refer to *pyhive* and *impyla* documentation for more details.
- **push_using_hive_cli** (*bool*) Whether the .*push()* operation should directly add files using *LOAD DATA LOCAL INPATH* rather than the *INSERT* operation via SQLAlchemy. Note that this requires the presence of the *hive* executable on the local PATH, or if connecting via a *RemoteClient* instance, on the remote's PATH. This is mostly useful for older versions of Hive which do not support the *INSERT* statement.
- **default_table_props** (*dict*) A dictionary of table properties to use by default when creating tables.
- **connection_options** (*dict*) Additional options to pass through to the .*connect*() methods of the drivers.

Attributes inherited from Duct:

protocol (str): The name of the protocol for which this instance was created (especially useful if a *Duct* subclass supports multiple protocols).

name (str): The name given to this Duct instance (defaults to class name).

- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS** (list<str>): The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init___(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)

- **session_properties (dict): A mapping of default session properties** to values. Interpretation is left up to implementations.
- templates (dict): A dictionary of name to template mappings. Additional templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dataframe_to_table (*df*, *table*, *if_exists='fail'*, ***kwargs*) Upload a local pandas dataframe into a table in this database.

Parameters

- **df** (pandas.DataFrame) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client._dataframe_to_table*.
- **HiveServer2Client Quirks:** If *use_hive_cli* (or if not specified *.push_using_hive_cli*) is *True*, a *CREATE TABLE* statement will be automatically generated based on the datatypes of the DataFrame (unless overwritten by *dtype_overrides*). The *DataFrame* will then be exported to a CSV compatible with Hive and uploaded (if necessary) to the remote, before being loaded into Hive using a *LOAD DATA LOCAL INFILE* ... query using the *hive* cli executable. Note that if a table is not partitioned, you cannot convert it to a partitioned table without deleting it first.

If *use_hive_cli* (or if not specified *.push_using_hive_cli*) is *False*, an attempt will be made to push the *DataFrame* to Hive using *pandas.DataFrame.to_sql* and the SQLAlchemy binding provided by *pyhive* and *impyla*. This may be slower, does not support older versions of Hive, and does not support table properties or partitioning.

If if the schema namespace is not specified, *table.schema* will be defaulted to your username.

Additional Args:

use_hive_cli (bool, None): A local override for the global .*push_using_hive_cli* attribute. If not specified, the global default is used. If True, then pushes are performed using the *hive* CLI executable on the local/remote PATH.

**kwargs (dict): Additional arguments to send to pandas.DataFrame.to_sql.

Further Parameters for CLI method (specifying these for the pandas method will cause a *RuntimeError* exception):

partition (dict): A mapping of column names to values that specify the partition into which the provided data should be uploaded, as well as providing the fields by which new tables should be partitioned.

sep (str): Field delimiter for data (defaults to CTRL-A, or *chr(1)*). table_props (dict): Properties to set on any newly created tables

(extends .*default_table_props*).

dtype_overrides (dict): Mapping of column names to Hive datatypes to use instead of default mapping.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

execute (*statement*, *wait=True*, *cursor=None*, *session_properties=None*, ***kwargs*) Execute a statement against this database and return a cursor object.

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- ****kwargs** (*dict*) Extra keyword arguments to be passed on to _*execute*, as implemented by subclasses.
- **template** (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (*bool*) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

HiveServer2Client Quirks:

Additional Args:

poll_interval (int): Default delay in seconds between consecutive query status (defaults to 1).

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template (*name*, *context=None*, ***kwargs*) Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol(protocol)

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '<*password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct_port*. You can change the remote port at runtime using: *duct.port* = *<port*>.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

- **HiveServer2Client Quirks:** This method may be overridden by subclasses, but provides the following default behaviour:
 - Ensures *self.registry*, *self.remote* and *self.cache* values are instances of the right types.
 - It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
 - It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
 - Ensures value of self.port is an integer (or None).

query (statement, format=None, format_opts={}, use_cache=True, **kwargs)

Execute a statement against this database and collect formatted data.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

query_from_file (file, fs=None, **kwargs)

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (*str*) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .query().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (statement, table, if_exists='fail', **kwargs)

Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client._query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%*hive*: For querying the database.
- %%hive.execute: For executing a statement against the database.
- %%hive.stream: For executing a statement against the database, and streaming the results.
- %%*hive.template*: The defining a new template.
- %%hive.render: Render a provided query statement.
- Line Magics:
 - %*hive*: For querying the database using a named template.
 - %hive.execute: For executing a named template statement against the database.
 - *%hive.stream*: For executing a named template against the database, and streaming the results.

- %hive.render: Render a provided a named template.
- %hive.desc: Describe the table nominated.
- %hive.head: Return the first rows in a specified table.
- %*hive.props*: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type *Duct* instance

schemas

An object with attributes corresponding to the names of the schemas in this database.

Type object

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

Parameters

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (*bool*) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream(statement, format=None, format_opts={}, batch=None, **kwargs)

Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

• **statement** (*str*) – The statement to be executed against the database.

- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc (table, renew=True, **kwargs)

Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop(table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

```
table_exists (table, renew=True, **kwargs)
```

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head (table, n=10, renew=True, **kwargs)

Retrieve the first *n* rows from a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols(table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

• **table** (*str*) – The table from which to extract data.

- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add (name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as *jinja2* templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type PrestoClient

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError - If name is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

template_render (name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False)

Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (*bool*) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (name_or_statement, by_name=False)

Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

Neo4jClient

class	<pre>omniduct.databases.neo4j.Neo4jClient(session_prop</pre>	erties=None, tem-
	plates=None	template_context=None,
default_format_opts=None, **kwargs)		
Bases: omniduct.databases.base.DatabaseClient		

This Duct connects to a Neo4j graph database server using the *neo4j* python library.

Attributes inherited from Duct:

protocol (str): The name of the protocol for which this instance was created (especially useful if a *Duct* subclass supports multiple protocols).

name (str): The name given to this Duct instance (defaults to class name).

- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

- __init__(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)
 - **session_properties (dict): A mapping of default session properties** to values. Interpretation is left up to implementations.
 - templates (dict): A dictionary of name to template mappings. Additional templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dataframe_to_table (*df*, *table*, *if_exists='fail'*, ***kwargs*) Upload a local pandas dataframe into a table in this database.

Parameters

- **df** (*pandas*.*DataFrame*) The dataframe to upload into the database.
- **table**(*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client._dataframe_to_table*.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

execute (*statement*, *wait=True*, *cursor=None*, *session_properties=None*, ***kwargs*) Execute a statement against this database and return a cursor object.

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- ****kwargs** (*dict*) Extra keyword arguments to be passed on to _*execute*, as implemented by subclasses.
- **template** (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]

- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (bool) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template (*name*, *context=None*, ***kwargs*) Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol(protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*cpassword*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: $duct.port = \langle port \rangle$.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

- **Neo4jClient Quirks:** This method may be overridden by subclasses, but provides the following default behaviour:
 - Ensures self.registry, self.remote and self.cache values are instances of the right types.
 - It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
 - It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
 - Ensures value of self.port is an integer (or None).

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.

- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

```
query_from_file (file, fs=None, **kwargs)
```

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (*str*) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*query*().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (*statement*, *table*, *if_exists='fail'*, ***kwargs*) Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client._query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- *%%hive*: For querying the database.
- %%hive.execute: For executing a statement against the database.
- *%%hive.stream*: For executing a statement against the database, and streaming the results.
- %%hive.template: The defining a new template.
- %%hive.render: Render a provided query statement.
- Line Magics:
 - %*hive*: For querying the database using a named template.
 - %hive.execute: For executing a named template statement against the database.
 - *%hive.stream*: For executing a named template against the database, and streaming the results.
 - %hive.render: Render a provided a named template.
 - %hive.desc: Describe the table nominated.
 - %hive.head: Return the first rows in a specified table.
 - %*hive.props*: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (bool) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream(statement, format=None, format_opts={}, batch=None, **kwargs)

Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc (*table*, *renew=True*, ***kwargs*) Describe a table in the database.

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).

• ****kwargs** (*dict*) – Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop (table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (dict) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_exists(table, renew=True, **kwargs)

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head (*table*, *n=10*, *renew=True*, ***kwargs*) Retrieve the first *n* rows from a table.

concove the first *n* flows from a t

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols(table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

- **table** (*str*) The table from which to extract data.
- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add(name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as *jinja2* templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type *PrestoClient*

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError – If name is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

template_render(name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False)

Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (name_or_statement, by_name=False)

Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

PrestoClient

Bases: omniauct.databases.base.Databaseclient, omniauct.databases._schema SchemasMixin

This Duct connects to a Facebook Presto server instance using the pyhive library.

In addition to the standard *DatabaseClient* API, *PrestoClient* adds a *.schemas* descriptor attribute, which enables a tab completion driven exploration of a Presto database's schemas and tables.

Attributes

- catalog (str) The default catalog to use in database queries.
- schema (str) The default schema/database to use in database queries.
- connection_options (dict) Additional options to pass on to pyhive.presto.connect(...).

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote** (None, omniduct.remotes.base.RemoteClient): A reference to a *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.

PROTOCOLS (list<str>): The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

- __init__(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)
 - **session_properties (dict): A mapping of default session properties** to values. Interpretation is left up to implementations.
 - **templates (dict): A dictionary of name to template mappings. Additional** templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

dataframe_to_table (df, table, if_exists='fail', **kwargs)

Upload a local pandas dataframe into a table in this database.

Parameters

- df (pandas.DataFrame) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client_dataframe_to_table.

PrestoClient Quirks: If if the schema namespace is not specified, *table.schema* will be defaulted to your username. Catalog overrides will be ignored, and will default to *self.catalog*.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

execute (*statement*, *wait=True*, *cursor=None*, *session_properties=None*, ***kwargs*) Execute a statement against this database and return a cursor object.

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- **kwargs (dict) Extra keyword arguments to be passed on to _execute, as implemented by subclasses.
- template (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (bool) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (*bool*) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

PrestoClient Quirks: If something goes wrong, *PrestoClient* will attempt to parse the error log and present the user with useful debugging information. If that fails, the full traceback will be raised instead.

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template(name, context=None, **kwargs)

Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol (protocol)

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this Duct instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: $duct.port = \langle port \rangle$.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

PrestoClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

query_from_file (file, fs=None, **kwargs)

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

query_from_template (name, context=None, **kwargs)
Render and then query using a named tempalte.

- **name** (*str*) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .query().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (*statement*, *table*, *if_exists='fail'*, ***kwargs*) Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client_query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%hive: For querying the database.
- %%hive.execute: For executing a statement against the database.
- %%hive.stream: For executing a statement against the database, and streaming the results.
- %%hive.template: The defining a new template.
- %%hive.render: Render a provided query statement.
- Line Magics:
 - %*hive*: For querying the database using a named template.
 - %hive.execute: For executing a named template statement against the database.
 - %hive.stream: For executing a named template against the database, and streaming the results.
 - %hive.render: Render a provided a named template.
 - %hive.desc: Describe the table nominated.
 - %hive.head: Return the first rows in a specified table.

- %hive.props: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type *Duct* instance

schemas

An object with attributes corresponding to the names of the schemas in this database.

Type object

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

Parameters

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (*bool*) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream (*statement*, *format=None*, *format_opts={}*, *batch=None*, ***kwargs*) Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.

- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc(table, renew=True, **kwargs)

Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop (table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_exists (*table*, *renew=True*, ***kwargs*) Check whether a table exists.

k whether a tabl

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head(table, n=10, renew=True, **kwargs)

Retrieve the first *n* rows from a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols (table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add (name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as jinja2 templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (str) The (typically) multiline body of the template.

Returns A reference to this object.

Return type *PrestoClient*

template_get (name)

Retrieve a named template.

Parameters name (str) – The name of the template to retrieve.

Raises ValueError - If name is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

template_render(name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False)

Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.
- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (name_or_statement, by_name=False)

Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '<*username*>'.

Type str

PySparkClient

Bases: omniduct.databases.base.DatabaseClient

This Duct connects to a local PySpark session using the pyspark library.

Attributes inherited from Duct:

protocol (str): The name of the protocol for which this instance was created (especially useful if a *Duct* subclass supports multiple protocols).

name (str): The name given to this Duct instance (defaults to class name).

host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).

port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote** (None, omniduct.remotes.base.RemoteClient): A reference to a *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

- ___init___(session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs) de
 - **session_properties (dict): A mapping of default session properties** to values. Interpretation is left up to implementations.
 - **templates (dict): A dictionary of name to template mappings. Additional** templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dataframe_to_table (*df, table, if_exists='fail', **kwargs*) Upload a local pandas dataframe into a table in this database.

Parameters

- **df** (*pandas*.*DataFrame*) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client._dataframe_to_table.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

execute (*statement*, *wait=True*, *cursor=None*, *session_properties=None*, ***kwargs*) Execute a statement against this database and return a cursor object.

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- ****kwargs** (*dict*) Extra keyword arguments to be passed on to _*execute*, as implemented by subclasses.
- template (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]

- **use_cache** (bool) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.execute*.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template(name, context=None, **kwargs)

Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol (protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this Duct instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '<*password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: *duct.port* = < port >.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

PySparkClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

eeute a statement against ans database and

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.

- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

```
query_from_file (file, fs=None, **kwargs)
```

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (*str*) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*query*().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (*statement*, *table*, *if_exists='fail'*, ***kwargs*) Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client._query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%*hive*: For querying the database.
- %%hive.execute: For executing a statement against the database.
- *%%hive.stream*: For executing a statement against the database, and streaming the results.
- %%*hive.template*: The defining a new template.
- %%hive.render: Render a provided query statement.
- Line Magics:
 - %*hive*: For querying the database using a named template.
 - %hive.execute: For executing a named template statement against the database.
 - *%hive.stream*: For executing a named template against the database, and streaming the results.
 - %hive.render: Render a provided a named template.
 - %hive.desc: Describe the table nominated.
 - %hive.head: Return the first rows in a specified table.
 - %hive.props: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

Parameters

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (*bool*) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream (*statement*, *format=None*, *format_opts={}*, *batch=None*, **kwargs) Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc (*table*, *renew=True*, ***kwargs*) Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).

• ****kwargs** (dict) – Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop (table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (dict) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_exists(table, renew=True, **kwargs)

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head (table, n=10, renew=True, **kwargs)

Retrieve the first n rows from a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols(table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add (name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as *jinja2* templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type PrestoClient

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError - If name is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

template_render(name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False)

Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (*name_or_statement*, *by_name=False*)

Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

SQLAlchemyClient

This Duct connects to several different databases using one of several SQLAlchemy drivers. In general, these are provided for their potential utility, but will be less functional than the specially crafted database clients.

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

NAMESPACE_DEFAULTS_READ

Backwards compatible shim for NAMESPACE_DEFAULTS.

NAMESPACE_DEFAULTS_WRITE

Unless overridden, this is the same as NAMESPACE_DEFAULTS_READ.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

___init__ (session_properties=None, templates=None, template_context=None, default_format_opts=None, **kwargs)

session_properties (dict): A mapping of default session properties to values. Interpretation is left up to implementations.

templates (dict): A dictionary of name to template mappings. Additional templates can be added using .template_add.

template_context (dict): The default template context to use when rendering templates.

default_format_opts (dict): The default formatting options passed to cursor formatter.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

dataframe_to_table (df, table, if_exists='fail', **kwargs)

Upload a local pandas dataframe into a table in this database.

Parameters

- **df** (pandas.DataFrame) The dataframe to upload into the database.
- **table** (*str*, *ParsedNamespaces*) The name of the table into which the dataframe should be uploaded.
- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (*dict*) Additional keyword arguments to pass onto *Database-Client._dataframe_to_table*.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

execute (*statement*, *wait=True*, *cursor=None*, *session_properties=None*, ***kwargs*) Execute a statement against this database and return a cursor object.

Where supported by database implementations, this cursor can the be used in future executions, by passing it as the *cursor* keyword argument.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- wait (bool) Whether the cursor should be returned before the server-side query computation is complete and the relevant results downloaded.
- **cursor** (*DBAP12* cursor) Rather than creating a new cursor, execute the statement against the provided cursor.
- **session_properties** (*dict*) Additional session properties and/or overrides to use for this query. Setting a session property value to *None* will cause it to be omitted.
- ****kwargs** (*dict*) Extra keyword arguments to be passed on to _*execute*, as implemented by subclasses.
- template (bool) Whether the statement should be treated as a Jinja2 template. [Used by *render_statement* decorator.]
- **context** (*dict*) The context in which the template should be evaluated (a dictionary of parameters to values). [Used by *render_statement* decorator.]
- **use_cache** (*bool*) True or False (default). Whether to use the cache (if present). [Used by *cached_method* decorator.]
- **renew** (bool) True or False (default). If cache is being used, renew it before returning stored value. [Used by *cached_method* decorator.]
- **cleanup** (bool) Whether statement should be cleaned up before computing the hash used to cache results. [Used by *cached_method* decorator.]

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_file (file, fs=None, **kwargs)

Execute a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (dict) Extra keyword arguments to pass on to DatabaseClient.execute.

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

execute_from_template(name, context=None, **kwargs)

Render and then execute a named template.

Parameters

- **name** (*str*) The name of the template to be rendered and executed.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*execute(*).

Returns A DBAPI2 compatible cursor instance.

Return type DBAPI2 cursor

classmethod for_protocol(protocol)

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = <port>.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

SQLAIchemyClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures *self.registry*, *self.remote* and *self.cache* values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.

- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

query (*statement*, *format=None*, *format_opts={}*, *use_cache=True*, ***kwargs*) Execute a statement against this database and collect formatted data.

Parameters

- **statement** (*str*) The statement to be executed by the query client (possibly templated).
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **use_cache** (*bool*) Whether to cache the cursor returned by *DatabaseClient.execute()* (overrides the default of False for *.execute()*). (default=True)
- ****kwargs** (*dict*) Additional arguments to pass on to *DatabaseClient.execute()*.

Returns The results of the query formatted as nominated.

query_from_file (file, fs=None, **kwargs)

Query using a statement stored in a file.

Parameters

- **file** (*str*, *file-like-object*) The path of the file containing the query statement to be executed against the database, or an open file-like resource.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** (*dict*) Extra keyword arguments to pass on to *DatabaseClient.query*.

Returns The results of the query formatted as nominated.

Return type object

query_from_template(name, context=None, **kwargs)

Render and then query using a named tempalte.

Parameters

- **name** (str) The name of the template to be rendered and used to query the database.
- **context** (*dict*) The context in which the template should be rendered.
- ****kwargs** (*dict*) Additional parameters to pass to .*query*().

Returns The results of the query formatted as nominated.

Return type object

query_to_table (statement, table, if_exists='fail', **kwargs)

Run a query and store the results in a table in this database.

Parameters

- **statement** The statement to be executed.
- **table** (*str*) The name of the table into which the dataframe should be uploaded.

- **if_exists** (*str*) if nominated table already exists: 'fail' to do nothing, 'replace' to drop, recreate and insert data into new table, and 'append' to add data from this table into the existing table.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client._query_to_table.

Returns The cursor object associated with the execution.

Return type DB-API cursor

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type Duct instance

register_magics(base_name=None)

The following magic functions will be registered (assuming that the base name is chosen to be 'hive'): - Cell Magics:

- %%*hive*: For querying the database.
- %%*hive.execute*: For executing a statement against the database.
- %%hive.stream: For executing a statement against the database, and streaming the results.
- %%hive.template: The defining a new template.
- %%hive.render: Render a provided query statement.

• Line Magics:

- %*hive*: For querying the database using a named template.
- %hive.execute: For executing a named template statement against the database.
- %*hive.stream*: For executing a named template against the database, and streaming the results.
- %hive.render: Render a provided a named template.
- %hive.desc: Describe the table nominated.
- %hive.head: Return the first rows in a specified table.
- %*hive.props*: Show the properties specified for a nominated table.

Documentation for these magics is provided online.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

schemas

An object with attributes corresponding to the names of the schemas in this database.

Type object

session_properties

The default session properties used in statement executions.

Type dict

classmethod statement_cleanup(statement)

Clean up statements prior to hash computation.

This classmethod takes an SQL statement and reformats it by consistently removing comments and replacing all whitespace. It is used by the *statement_hash* method to avoid functionally identical queries hitting different cache keys. If the statement's language is not to be SQL, this method should be overloaded appropriately.

Parameters statement (*str*) – The statement to be reformatted/cleaned-up.

Returns The new statement, consistently reformatted.

Return type str

classmethod statement_hash(statement, cleanup=True)

Retrieve the hash to use to identify query statements to the cache.

Parameters

- **statement** (*str*) A string representation of the statement to be hashed.
- **cleanup** (bool) Whether the statement should first be consistently reformatted using *statement_cleanup*.

Returns The hash used to identify a statement to the cache.

Return type str

stream(statement, format=None, format_opts={}, batch=None, **kwargs)

Execute a statement against this database and stream formatted results.

This method returns a generator over objects representing rows in the result set. If *batch* is not *None*, then the iterator will be over lists of length *batch* containing formatted rows.

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **format** (*str*) A subclass of CursorFormatter, or one of: 'pandas', 'hive', 'csv', 'tuple' or 'dict'. Defaults to *self.DEFAULT_CURSOR_FORMATTER*.
- **format_opts** (*dict*) A dictionary of format-specific options.
- **batch** (*int*) If not *None*, the number of rows from the resulting cursor to be returned at once.
- ****kwargs** (dict) Additional keyword arguments to pass onto Database-Client.execute.

Returns

An iterator over objects of the nominated format or, if batched, a list of such objects.

Return type iterator

stream_to_file (statement, file, format='csv', fs=None, **kwargs)

Execute a statement against this database and stream results to a file.

This method is a wrapper around *DatabaseClient.stream* that enables the iterative writing of cursor results to a file. This is especially useful when there are a very large number of results, and loading them all into

memory would require considerable resources. Note that 'csv' is the default format for this method (rather than *pandas*).

Parameters

- **statement** (*str*) The statement to be executed against the database.
- **file** (*str*, *file-like-object*) The filename where the data should be written, or an open file-like resource.
- **format** (*str*) The format to be used ('csv' by default). Format options can be passed via ***kwargs*.
- **fs** (*None*, FileSystemClient) The filesystem wihin which the nominated file should be found. If *None*, the local filesystem will be used.
- ****kwargs** Additional keyword arguments to pass onto *DatabaseClient.stream*.

table_desc (table, renew=True, **kwargs)

Describe a table in the database.

Parameters

- **table** (*str*) The table to describe.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A dataframe description of the table.

Return type pandas.DataFrame

table_drop(table, **kwargs)

Remove a table from the database.

Parameters

- **table** (*str*) The table to drop.
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The cursor associated with this execution.

Return type DB-API cursor

table_exists (table, renew=True, **kwargs)

Check whether a table exists.

Parameters

- **table** (*str*) The table for which to check.
- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns True if table exists, and False otherwise.

Return type bool

table_head (table, n=10, renew=True, **kwargs)

Retrieve the first *n* rows from a table.

Parameters

- **table** (*str*) The table from which to extract data.
- **n** (*int*) The number of rows to extract.

- **renew** (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the first *n* rows of the nominated table.

Return type pandas.DataFrame

table_list (namespace=None, renew=True, **kwargs)

Return a list of table names in the data source as a DataFrame.

Parameters

- **namespace** (*str*) The namespace in which to look for tables.
- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns The names of schemas in this database.

Return type list<str>

table_partition_cols (table, renew=True, **kwargs)

Extract the columns by which a table is partitioned (if database supports partitions).

Parameters

- **table** (*str*) The table from which to extract data.
- **renew** (bool) Whether to renew the results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns A list of columns by which table is partitioned.

Return type list<str>

table_props (table, renew=True, **kwargs)

Retrieve the properties associated with a table.

Parameters

- **table** (*str*) The table from which to extract data.
- renew (bool) Whether to renew the table list or use cached results (default: True).
- ****kwargs** (*dict*) Additional arguments passed through to implementation.

Returns

A dataframe representation of the table properties.

Return type pandas.DataFrame

template_add(name, body)

Add a named template to the internal dictionary of templates.

Note: Templates are interpreted as jinja2 templates. See .template_render for more information.

Parameters

- **name** (*str*) The name of the template.
- **body** (*str*) The (typically) multiline body of the template.

Returns A reference to this object.

Return type PrestoClient

template_get (name)

Retrieve a named template.

Parameters name (*str*) – The name of the template to retrieve.

Raises ValueError - If name is not associated with a template.

Returns The requested template.

Return type str

template_names

A list of names associated with the templates associated with this client.

Type list

template_render (name_or_statement, context=None, by_name=False, cleanup=False, meta_only=False) Render a template by name or value.

In addition to the *jinja2* templating syntax, described in more detail in the official *jinja2* documentation, a meta-templating extension is also provided. This meta-templating allows you to reference other reference other templates. For example, if you had two SQL templates named 'template_a' and 'template_b', then you could render them into one SQL query using (for example):

Note that template substitution in this way is iterative, so you can chain template embedding, provided that such embedding is not recursive.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **context** (*dict*, *None*) A dictionary to use as the template context. If not specified, an empty dictionary is used.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.
- **cleanup** (bool) *True* if the rendered statement should be formatted, *False* (default) otherwise
- **meta_only** (bool) *True* if rendering should only progress as far as rendering nested templates (i.e. don't actually substitute in variables from the context); *False* (default) otherwise.

Returns The rendered template.

Return type str

template_variables (*name_or_statement*, *by_name=False*) Return the set of undeclared variables required for this template.

Parameters

- **name_or_statement** (*str*) The name of a template (if *by_name* is True) or else a string representation of a *jinja2* template.
- **by_name** (bool) *True* if *name_or_statement* should be interpreted as a template name, or *False* (default) if *name_or_statement* should be interpreted as a template body.

Returns A set of names which the template requires to be rendered.

Return type set<str>

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

5.3 Filesystems

All database clients are expected to be subclasses of *DatabaseClient*, and so will share a common API and inherit a suite of IPython magics. Protocol implementations are also free to add extra methods, which are documented in the "Subclass Reference" section below.

5.3.1 Common API

An abstract class providing the common API for all filesystem clients.

Class Attributes

- **DUCT_TYPE** (*Duct.Type*) The type of *Duct* protocol implemented by this class.
- **DEFAULT_PORT** (*int*) The default port for the filesystem service (defined by subclasses).

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

__init___(cwd=None, home=None, read_only=False, global_writes=False, **kwargs)

- **cwd** (None, str): The path prefix to use as the current working directory (if None, the user's home directory is used where that makes sense).
- **home (None, str): The path prefix to use as the current users' home** directory. If not specified, it will default to an implementation- specific value (often '/').

read_only (bool): Whether the filesystem should only be able to perform read operations.

global_writes (bool): Whether to allow writes outside of the user's home folder.

**kwargs (dict): Additional keyword arguments to passed on to subclasses.

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

- path (str) The base path to which components should be joined.
- ***components** (*str*) Any additional components to join to the base path.

Returns The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_basename(path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (*str*) – The path from which the basename should be extracted.

Returns The extracted basename.

Return type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (str) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to path on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

exists(path)

Check whether nominated path exists on this filesytem.

Parameters path (str) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns True if folder exists at nominated path, and False otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns *True* if a file exists at nominated path, and *False* otherwise.

Return type bool

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

This method should return a generator over FileSystemFileDesc objects.

listdir(path=None)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (cpath name>, [<directory 1>, ...], [<file 1>, ...])

Parameters path (*str*) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- path_prefix (str) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

mkdir (*path*, *recursive=True*, *exist_ok=False*) Create a directory at the given path.

Parameters

- **path** (*str*) The path of the directory to create.
- **recursive** (*bool*) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless *recursive* is set to *True*.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- **recursive** (bool) Whether to remove directories and all of their contents.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type *FileSystemFile* or file-like

download (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (str) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (*str*) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

upload (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem fs to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to fs.download(..., fs=self).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- dest (str) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

- FileSystemClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:
 - Ensures self.registry, self.remote and self.cache values are instances of the right types.
 - It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
 - It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
 - Ensures value of self.port is an integer (or None).

```
class omniduct.filesystems.base.FileSystemFile(fs, path, mode='r')
Bases: object
```

A file-like implementation that is interchangeable with native Python file objects, allowing remote files to be treated identically to local files both by omniduct, the user and other libraries.

```
___init__ (fs, path, mode='r')
```

Initialize self. See help(type(self)) for accurate signature.

```
class omniduct.filesystems.base.FileSystemFileDesc
Bases: omniduct.filesystems.base.Node
```

A representation of a file/directory stored within an Omniduct FileSystemClient.

5.3.2 Subclass Reference

For comprehensive documentation on any particular subclass, please refer to one of the below documents.

LocalFsClient

LocalFsClient is a Duct that implements the FileSystemClient common API, and exposes the local filesystem.

Unlike most other filesystems, *LocalFsClient* defaults to the current working directory on the local machine, rather than the home directory as used on remote filesystems. To change this, you can always execute: `local_fs.path_cwd = local_fs.path_home `

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.

DUCT_TYPE (Duct.Type): The type of *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.

PROTOCOLS (list<str>): The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (cwd=None, home=None, read_only=False, global_writes=False, **kwargs)

- **cwd** (None, str): The path prefix to use as the current working directory (if None, the user's home directory is used where that makes sense).
- **home (None, str): The path prefix to use as the current users' home** directory. If not specified, it will default to an implementation- specific value (often '/').

read_only (bool): Whether the filesystem should only be able to perform read operations.

global_writes (bool): Whether to allow writes outside of the user's home folder.

******kwargs (dict): Additional keyword arguments to passed on to subclasses.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

```
download (source, dest=None, overwrite=False, fs=None)
```

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (*str*) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (str) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

exists (path)

Check whether nominated path exists on this filesytem.

Parameters path (*str*) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- **path_prefix** (*str*) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

classmethod for_protocol (protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<host>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns *True* if folder exists at nominated path, and *False* otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns *True* if a file exists at nominated path, and *False* otherwise.

Return type bool

listdir (*path=None*)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

mkdir (path, recursive=True, exist_ok=False)

Create a directory at the given path.

Parameters

- **path** (*str*) The path of the directory to create.
- **recursive** (bool) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type FileSystemFile or file-like

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

path_basename(path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (*str*) – The path from which the basename should be extracted.

Returns The extracted basename.

Return type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (*str*) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

- **path** (*str*) The base path to which components should be joined.
- ***components** (*str*) Any additional components to join to the base path.

Returns The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to *path* on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = < port >.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type Duct instance

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- **recursive** (bool) Whether to remove directories and all of their contents.

reset()

Reset this *Duct* instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

```
upload (source, dest=None, overwrite=False, fs=None)
```

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem fs to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to fs.download(..., fs=self).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest** (*str*) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (bool) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (result are an example of the second sec

Parameters path (*str*) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

S3Client

This Duct connects to an Amazon S3 bucket instance using the *boto3* library. Authentication is (optionally) handled using *opinel*.

Attributes

- **bucket** (*str*) The name of the Amazon S3 bucket to use.
- **aws_profile** (*str*) The name of configured AWS profile to use. This should refer to the name of a profile configured in, for example, ~/*.aws/credentials*. Authentication is handled by the *opinel* library, which is also aware of environment variables.

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.
Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (cwd=None, home=None, read_only=False, global_writes=False, **kwargs)

- **cwd** (None, str): The path prefix to use as the current working directory (if None, the user's home directory is used where that makes sense).
- **home (None, str): The path prefix to use as the current users' home** directory. If not specified, it will default to an implementation- specific value (often '/').

read_only (bool): Whether the filesystem should only be able to perform read operations.

global_writes (bool): Whether to allow writes outside of the user's home folder.

**kwargs (dict): Additional keyword arguments to passed on to subclasses.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

download (*source*, *dest=None*, *overwrite=False*, *fs=None*) Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (*str*) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (*str*) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (bool) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

exists (path)

Check whether nominated path exists on this filesytem.

Parameters path (*str*) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- **path_prefix** (*str*) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

```
classmethod for_protocol(protocol)
```

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns True if folder exists at nominated path, and False otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns True if a file exists at nominated path, and False otherwise.

Return type bool

listdir(path=None)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

mkdir (*path*, *recursive=True*, *exist_ok=False*) Create a directory at the given path.

Parameters

- path (str) The path of the directory to create.
- **recursive** (bool) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type FileSystemFile or file-like

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*cpassword*'.

Type str

path_basename (path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (str) – The path from which the basename should be extracted.

Returns The extracted basename.

Return type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (str) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

• **path** (*str*) – The base path to which components should be joined.

• ***components** (*str*) – Any additional components to join to the base path.

Returns The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to path on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct_port*. You can change the remote port at runtime using: *duct.port* = *<port*>.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

S3Client Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

• Ensures *self.registry*, *self.remote* and *self.cache* values are instances of the right types.

- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- **recursive** (bool) Whether to remove directories and all of their contents.

reset()

Reset this *Duct* instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type *Duct* instance

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

upload (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem fs to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to fs.download(..., fs=self).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest** (str) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (bool) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (cpath name>, [<directory 1>, ...], [<file 1>, ...])

Parameters path (*str*) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

WebHdfsClient

Bases: omniduct.filesystems.base.FileSystemClient

This Duct connects to an Apache WebHDFS server using the pywebhdfs library.

Attributes namenodes (*list<str>*) – A list of hosts that are acting as namenodes for the HDFS cluster in form "<hostname>:<port>".

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (cwd=None, home=None, read_only=False, global_writes=False, **kwargs)

- **cwd** (None, str): The path prefix to use as the current working directory (if None, the user's home directory is used where that makes sense).
- **home (None, str): The path prefix to use as the current users' home** directory. If not specified, it will default to an implementation- specific value (often '/').
- read_only (bool): Whether the filesystem should only be able to perform read operations.
- global_writes (bool): Whether to allow writes outside of the user's home folder.

**kwargs (dict): Additional keyword arguments to passed on to subclasses.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

download (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (*str*) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (*str*) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

exists (path)

Check whether nominated path exists on this filesytem.

Parameters path (*str*) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- **path_prefix** (*str*) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

classmethod for_protocol (protocol)

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown - If no class has been defined that offers the named protocol.

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns *True* if folder exists at nominated path, and *False* otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns True if a file exists at nominated path, and False otherwise.

Return type bool

listdir(path=None)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

mkdir (path, recursive=True, exist_ok=False)

Create a directory at the given path.

Parameters

- **path** (*str*) The path of the directory to create.
- **recursive** (bool) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (*path*, *mode*='*rt*')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type FileSystemFile or file-like

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

path_basename(path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (*str*) – The path from which the basename should be extracted.

Returns The extracted basename.

Return type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (*str*) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

- **path** (*str*) The base path to which components should be joined.
- ***components** (*str*) Any additional components to join to the base path.
- **Returns** The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to *path* on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = <port>.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

- **WebHdfsClient Quirks:** This method may be overridden by subclasses, but provides the following default behaviour:
 - Ensures self.registry, self.remote and self.cache values are instances of the right types.
 - It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
 - It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
 - Ensures value of self.port is an integer (or None).

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- recursive (bool) Whether to remove directories and all of their contents.

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

upload (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem fs to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to fs.download(..., fs=self).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest** (*str*) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = (<username>).

Type str

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (path name>, [<directory 1>, ...], [<file 1>, ...])

Parameters path (str) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

5.4 Remotes

All remote clients are expected to be subclasses of *RemoteClient*, and so will share a common API. Protocol implementations are also free to add extra methods, which are documented in the "Subclass Reference" section below.

5.4.1 Common API

class omniduct.remotes.base.RemoteClient(smartcards=None, **kwargs)
 Bases: omniduct.filesystems.base.FileSystemClient

An abstract class providing the common API for all remote clients.

- Attributes smartcard (*dict*) Mapping of smartcard names to system libraries compatible with *ssh-add -s* '*<system library>*'....
- Attributes smartcard (*dict*) Mapping of smartcard names to system libraries compatible with *ssh-add -s* '*<system library>*'....

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- **host (str): The host name providing the service (will be '127.0.0.1', if** service is port forwarded from remote; use ._*host* to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

__init___(smartcards=None, **kwargs)

Parameters smartcards (*dict*) – Mapping of smartcard names to system libraries compatible with *ssh-add -s* '*<system library>*'....

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

RemoteClient Quirks: Connect to the remote server.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Compared to base *Duct.connect*, this method will automatically catch the first *DuctAuthentication*-*Error* error triggered by *Duct.connect*, and (if smartcards have been configured) attempt to re-initialise the smartcards before trying once more.

Returns: Duct instance: A reference to the current object.

prepare_smartcards()

Prepare smartcards for use in authentication.

This method checks attempts to ensure that the each of the nominated smartcards is available and prepared for use. This may result in interactive requests for pin confirmation, depending on the card.

Returns

Returns True if at least one smartcard was activated, and False otherwise.

Return type bool

execute (cmd, **kwargs)

Execute a command on the remote server.

Parameters

- cmd(str) The command to run on the remote associated with this instance.
- ****kwargs** (*dict*) Additional keyword arguments to be passed on to ._*execute*.

Returns The result of the execution.

Return type SubprocessResults

port_forward (remote_host, remote_port=None, local_port=None)

Initiate a port forward connection.

This method establishes a local port forwarding from a local port *local* to remote port *remote*. If *local* is *None*, an available local port is automatically chosen. If the remote port is already forwarded, a new connection is not established.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port to use locally (automatically determined if not specified).

Returns The local port which is port forwarded to the remote service.

Return type int

has_port_forward (remote_host=None, remote_port=None, local_port=None)
Check whether a port forward connection exists.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port used locally.

Returns

Whether a port-forward for this remote service exists, or if local port is specified, whether that port is locally used for port forwarding.

Return type bool

```
port_forward_stop (local_port=None, remote_host=None, remote_port=None)
```

Disconnect an existing port forward connection.

If a local port is provided, then the forwarding (if any) associated with that port is found and stopped; otherwise any established port forwarding associated with the nominated remote service is stopped.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- local_port (int, None) The port used locally.

port_forward_stopall()

Disconnect all existing port forwarding connections.

get_local_uri(uri)

Convert a remote uri to a local one.

This method takes a remote service uri accessible to the remote host and returns a local uri accessible directly on the local host, establishing any necessary port forwarding in the process.

Parameters uri (*str*) – The remote uri to be made local.

Returns A local uri that tunnels all traffic to the remote host.

Return type str

show_port_forwards()

Print to stdout the active port forwards associated with this client.

is_port_bound(host, port)

Check whether a port on a remote host is accessible.

This method checks to see whether a particular port is active on a given host by attempting to establish a connection with it.

Parameters

- **host** (*str*) The hostname of the target service.
- **port** (*int*) The port of the target service.

Returns Whether the port is active and accepting connections.

Return type bool

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (str) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

RemoteClient Quirks: This method should return a generator over FileSystemFileDesc objects.

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

download (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (str) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (str) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

exists(path)

Check whether nominated path exists on this filesytem.

Parameters path (*str*) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- **path_prefix** (*str*) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns True if folder exists at nominated path, and False otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns True if a file exists at nominated path, and False otherwise.

Return type bool

mkdir (path, recursive=True, exist_ok=False)

Create a directory at the given path.

Parameters

- **path** (*str*) The path of the directory to create.
- **recursive** (*bool*) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type *FileSystemFile* or file-like

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

RemoteClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- **recursive** (bool) Whether to remove directories and all of their contents.

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (path name>, [<directory 1>, ...], [<file 1>, ...])

Parameters path (*str*) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

5.4.2 Subclass Reference

For comprehensive documentation on any particular subclass, please refer to one of the below documents.

SSHClient

class omniduct.remotes.ssh.SSHClient (smartcards=None, **kwargs)
Bases: omniduct.remotes.base.RemoteClient

An implementation of the *RemoteClient Duct*, offering a persistent connection to remote hosts over SSH via the CLI. As such, it requires that *ssh* be installed and on your executable path.

To speed up connections we use control sockets, which allows all connections to share one SSH transport. For more details, refer to: https://puppetlabs.com/blog/speed-up-ssh-by-reusing-connections

Attributes interactive (*bool*) – Whether *SSHClient* should ask the user questions, if necessary, to establish the connection. Production deployments using this client should set this to False. (default: *False*)

Attributes inherited from RemoteClient:

smartcard (dict): Mapping of smartcard names to system libraries compatible with ssh-add -s '<system library>'....

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.

- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (smartcards=None, **kwargs)

Parameters smartcards (*dict*) – Mapping of smartcard names to system libraries compatible with *ssh-add -s* '*<system library>*'....

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

RemoteClient Quirks: Connect to the remote server.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Compared to base *Duct.connect*, this method will automatically catch the first *DuctAuthentication*-*Error* error triggered by *Duct.connect*, and (if smartcards have been configured) attempt to re-initialise the smartcards before trying once more.

Returns: Duct instance: A reference to the current object.

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

download (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (str) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (*str*) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (bool) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

SSHClient Quirks: Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesytem *fs*, overwriting any existing file if *overwrite* is *True*.

Args:

- **source (str): The path on this filesystem of the file to download to** the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest (str): The destination path on filesystem (***fs***). If not** specified, the file/folder is uploaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- overwrite (bool): *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs (FileSystemClient): The FileSystemClient into which the nominated** file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

SSHClient Quirks: This method is overloaded so that remote-to-local downloads can be handled specially using *scp*. Downloads to any non-local filesystem are handled using the standard implementation.

execute (cmd, **kwargs)

Execute a command on the remote server.

Parameters

- cmd(str) The command to run on the remote associated with this instance.
- ****kwargs** (*dict*) Additional keyword arguments to be passed on to ._*execute*.

Returns The result of the execution.

Return type SubprocessResults

SSHClient Quirks:

Additional Args:

skip_cwd (bool): Whether to skip changing to the current working directory associated with this client before executing the command. This is mainly useful to methods internal to this class.

exists (path)

Check whether nominated path exists on this filesytem.

Parameters path (str) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- path_prefix (str) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

```
classmethod for_protocol (protocol)
```

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

get_local_uri(uri)

Convert a remote uri to a local one.

This method takes a remote service uri accessible to the remote host and returns a local uri accessible directly on the local host, establishing any necessary port forwarding in the process.

Parameters uri (str) – The remote uri to be made local.

Returns A local uri that tunnels all traffic to the remote host.

Return type str

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

has_port_forward (remote_host=None, remote_port=None, local_port=None)
Check whether a port forward connection exists.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- local_port (int, None) The port used locally.

Returns

Whether a port-forward for this remote service exists, or if local port is specified, whether that port is locally used for port forwarding.

Return type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct_host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

is_port_bound(host, port)

Check whether a port on a remote host is accessible.

This method checks to see whether a particular port is active on a given host by attempting to establish a connection with it.

Parameters

- **host** (*str*) The hostname of the target service.
- **port** (*int*) The port of the target service.

Returns Whether the port is active and accepting connections.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns *True* if folder exists at nominated path, and *False* otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (str) – The path for which to check file nature.

Returns True if a file exists at nominated path, and False otherwise.

Return type bool

listdir (*path=None*)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

mkdir (*path*, *recursive=True*, *exist_ok=False*) Create a directory at the given path.

Parameters

- path (str) The path of the directory to create.
- **recursive** (bool) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

• **path** (*str*) – The path of the file to open.

• mode (str) - All standard Python file modes.

Returns An opened file-like object.

Return type *FileSystemFile* or file-like

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

path_basename(path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (str) – The path from which the basename should be extracted.

Returns The extracted basename.

Return type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (*str*) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

- **path** (*str*) The base path to which components should be joined.
- ***components** (*str*) Any additional components to join to the base path.

Returns The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to path on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = <port>.

Type int

port_forward(remote_host, remote_port=None, local_port=None)

Initiate a port forward connection.

This method establishes a local port forwarding from a local port *local* to remote port *remote*. If *local* is *None*, an available local port is automatically chosen. If the remote port is already forwarded, a new connection is not established.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port to use locally (automatically determined if not specified).

Returns The local port which is port forwarded to the remote service.

Return type int

port_forward_stop (local_port=None, remote_host=None, remote_port=None)

Disconnect an existing port forward connection.

If a local port is provided, then the forwarding (if any) associated with that port is found and stopped; otherwise any established port forwarding associated with the nominated remote service is stopped.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- local_port (*int*, *None*) The port used locally.

port_forward_stopall()

Disconnect all existing port forwarding connections.

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

SSHClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

prepare_smartcards()

Prepare smartcards for use in authentication.

This method checks attempts to ensure that the each of the nominated smartcards is available and prepared for use. This may result in interactive requests for pin confirmation, depending on the card.

Returns

Returns True if at least one smartcard was activated, and False otherwise.

Return type bool

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- recursive (bool) Whether to remove directories and all of their contents.

reset()

Reset this *Duct* instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

show_port_forwards()

Print to stdout the active port forwards associated with this client.

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

update_host_keys()

Update host keys associated with this remote.

This method updates the SSH host-keys stored in ~/.ssh/known_hosts, allowing one to successfully connect to hosts when servers are, for example, redeployed and have different host keys.

upload (source, dest=None, overwrite=False, fs=None)

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem fs to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to fs.download(..., fs=self).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest** (str) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (bool) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

SSHClient Quirks: Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem *fs* to the path *dest* on this filesytem, overwriting any existing file if *overwrite* is *True*. This is equivalent to *fs.download*(..., *fs=self*).

Args:

- **source (str): The path on the specified filesystem (***fs***) of the** file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest (str): The destination path on this filesystem. If not** specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then

file will be copied into destination folder, and will throw an error if path does not resolve to a directory.

- **overwrite** (**bool**): *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- fs (FileSystemClient): The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.
- **SSHClient Quirks:** This method is overloaded so that local-to-remote uploads can be handled specially using *scp*. Uploads to any non-local filesystem are handled using the standard implementation.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (cpath name>, [<directory 1>, ...], [<file 1>, ...])

Parameters path (*str*) – The path of the directory from which to enumerate contents.

Returns A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

ParamikoSSHClient

Bases: omniduct.remotes.base.RemoteClient

An experimental SSH client that uses a *paramiko* rather than command-line SSH backend. This client has been fully implemented and should work as is, but until it receives further testing, we recommend using the cli backed SSH client.

Attributes inherited from RemoteClient:

smartcard (dict): Mapping of smartcard names to system libraries compatible with ssh-add -s '<system library>'....

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.

- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__ (smartcards=None, **kwargs)

Parameters smartcards (*dict*) – Mapping of smartcard names to system libraries compatible with *ssh-add -s* '*<system library>*'....

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

RemoteClient Quirks: Connect to the remote server.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Compared to base *Duct.connect*, this method will automatically catch the first *DuctAuthentication*-*Error* error triggered by *Duct.connect*, and (if smartcards have been configured) attempt to re-initialise the smartcards before trying once more. Returns: Duct instance: A reference to the current object.

dir (path=None)

Retrieve information about the children of a nominated directory.

This method returns a generator over *FileSystemFileDesc* objects that represent the files/directories that a present as children of the nominated path. If *path* is not a directory, an exception is raised. The path is interpreted as being relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path to examine for children.

Returns The children of *path* represented as *FileSystemFileDesc* objects.

Return type generator<FileSystemFileDesc>

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

download (source, dest=None, overwrite=False, fs=None)

Download files to another filesystem.

This method (recursively) downloads a file/folder from path *source* on this filesystem to the path *dest* on filesystem *fs*, overwriting any existing file if *overwrite* is *True*.

Parameters

- **source** (*str*) The path on this filesystem of the file to download to the nominated filesystem (*fs*). If *source* ends with '/' then contents of the the *source* directory will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **dest** (*str*) The destination path on filesystem (*fs*). If not specified, the file/folder is downloaded into the default path, usually one's home folder. If *dest* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder. If *dest* is otherwise a directory, an exception will be raised.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient into which the nominated file/folder *source* should be downloaded. If not specified, defaults to the local filesystem.

execute (cmd, **kwargs)

Execute a command on the remote server.

Parameters

- cmd(str) The command to run on the remote associated with this instance.
- ****kwargs** (*dict*) Additional keyword arguments to be passed on to ._execute.

Returns The result of the execution.

Return type SubprocessResults

exists(path)

Check whether nominated path exists on this filesytem.

Parameters path (*str*) – The path for which to check existence.

Returns

True if file/folder exists at nominated path, and False otherwise.

Return type bool

find (path_prefix=None, **attrs)

Find a file or directory based on certain attributes.

This method searches for files or folders which satisfy certain constraints on the attributes of the file (as encoded into *FileSystemFileDesc*). Note that without attribute constraints, this method will function identically to *self.dir*.

Parameters

- **path_prefix** (*str*) The path under which files/directories should be found.
- ****attrs** (*dict*) Constraints on the fields of the *FileSystemFileDesc* objects associated with this filesystem, as constant values or callable objects (in which case the object will be called and should return True if attribute value is match, and False otherwise).

Returns

A generator over *FileSystemFileDesc* objects that are descendents of *path_prefix* and which statisfy provided constraints.

Return type generator<FileSystemFileDesc>

classmethod for_protocol (protocol)

Retrieve a *Duct* subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

get_local_uri (uri)

Convert a remote uri to a local one.

This method takes a remote service uri accessible to the remote host and returns a local uri accessible directly on the local host, establishing any necessary port forwarding in the process.

Parameters uri (*str*) – The remote uri to be made local.

Returns A local uri that tunnels all traffic to the remote host.

Return type str

global_writes

Whether writes should be permitted outside of home directory. This write-lock is designed to prevent inadvertent scripted writing in potentially dangerous places.

Type bool

has_port_forward (remote_host=None, remote_port=None, local_port=None) Check whether a port forward connection exists.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port used locally.

Returns

Whether a port-forward for this remote service exists, or if local port is specified, whether that port is locally used for port forwarding.

Return type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct_host*, and change the remote host at runtime using: *duct.host* = '<host>'.

Type str

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

is_port_bound(host, port)

Check whether a port on a remote host is accessible.

This method checks to see whether a particular port is active on a given host by attempting to establish a connection with it.

Parameters

- **host** (*str*) The hostname of the target service.
- **port** (*int*) The port of the target service.

Returns Whether the port is active and accepting connections.

Return type bool

isdir(path)

Check whether a nominated path is directory.

Parameters path (*str*) – The path for which to check directory nature.

Returns *True* if folder exists at nominated path, and *False* otherwise.

Return type bool

isfile(path)

Check whether a nominated path is a file.

Parameters path (*str*) – The path for which to check file nature.

Returns True if a file exists at nominated path, and False otherwise.

Return type bool

listdir(path=None)

Retrieve the names of the children of a nomianted directory.

This method inspects the contents of a directory using *.dir(path)*, and returns the names of child members as strings. *path* is interpreted relative to the current working directory (on remote filesytems, this will typically be the home folder).

Parameters path (*str*) – The path of the directory from which to enumerate filenames.

Returns The names of all children of the nominated directory.

Return type list<str>

mkdir (path, recursive=True, exist_ok=False)

Create a directory at the given path.

Parameters

- **path** (*str*) The path of the directory to create.
- **recursive** (bool) Whether to recursively create any parents of this path if they do not already exist.

Note: *exist_ok* is passed onto subclass implementations of *_mkdir* rather that implementing the existence check using *.exists* so that they can avoid the overhead associated with multiple operations, which can be costly in some cases.

open (path, mode='rt')

Open a file for reading and/or writing.

This method opens the file at the given path for reading and/or writing operations. The object returned is programmatically interchangeable with any other Python file-like object, including specification of file modes. If the file is opened in write mode, changes will only be flushed to the source filesystem when the file is closed.

Parameters

- **path** (*str*) The path of the file to open.
- mode (*str*) All standard Python file modes.

Returns An opened file-like object.

Return type FileSystemFile or file-like

ParamikoSSHClient Quirks: Paramiko offers a complete file-like abstraction for files opened over sftp, so we use that abstraction rather than a *FileSystemFile*. Results should be indistinguishable.

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '<*password*>'.

Type str

path_basename(path)

Extract the last component of a given path.

Components are determined by splitting by *self.path_separator*. Note that if a path ends with a path separator, the basename will be the empty string.

Parameters path (*str*) – The path from which the basename should be extracted.
Returns The extracted basename.

Return type str

path_cwd

The path prefix associated with the current working directory. If not otherwise set, it will be the users' home directory, and will be the prefix used by all non-absolute path references on this filesystem.

Type str

path_dirname (path)

Extract the parent directory for provided path.

This method returns the entire path except for the basename (the last component), where components are determined by splitting by *self.path_separator*.

Parameters path (*str*) – The path from which the directory path should be extracted.

Returns The extracted directory path.

Return type str

path_home

The path prefix to use as the current users' home directory. Unless *cwd* is set, this will be the prefix to use for all non-absolute path references on this filesystem. This is assumed not to change between connections, and so will not be updated on client reconnections. Unless *global_writes* is set to *True*, this will be the only folder into which this client is permitted to write.

Type str

path_join (path, *components)

Generate a new path by joining together multiple paths.

If any component starts with *self.path_separator* or '~', then all previous path components are discarded, and the effective base path becomes that component (with '~' expanding to *self.path_home*). Note that this method does *not* simplify paths components like '..'. Use *self.path_normpath* for this purpose.

Parameters

- **path** (*str*) The base path to which components should be joined.
- ***components** (*str*) Any additional components to join to the base path.

Returns The path resulting from joining all of the components nominated, in order, to the base path.

Return type str

path_normpath(path)

Normalise a pathname.

This method returns the normalised (absolute) path corresponding to *path* on this filesystem.

Parameters path (*str*) – The path to normalise (make absolute).

Returns The normalised path.

Return type str

path_separator

The character(s) to use in separating path components. Typically this will be '/'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct_port*. You can change the remote port at runtime using: *duct.port* = *<port*>.

Type int

port_forward(remote_host, remote_port=None, local_port=None)

Initiate a port forward connection.

This method establishes a local port forwarding from a local port *local* to remote port *remote*. If *local* is *None*, an available local port is automatically chosen. If the remote port is already forwarded, a new connection is not established.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port to use locally (automatically determined if not specified).

Returns The local port which is port forwarded to the remote service.

Return type int

```
port_forward_stop (local_port=None, remote_host=None, remote_port=None)
```

Disconnect an existing port forward connection.

If a local port is provided, then the forwarding (if any) associated with that port is found and stopped; otherwise any established port forwarding associated with the nominated remote service is stopped.

Parameters

- **remote_host** (*str*) The hostname of the remote host in form: 'hostname(:port)'.
- **remote_port** (*int*, *None*) The remote port of the service.
- **local_port** (*int*, *None*) The port used locally.

port_forward_stopall()

Disconnect all existing port forwarding connections.

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

ParamikoSSHClient Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.

• Ensures value of self.port is an integer (or None).

prepare_smartcards()

Prepare smartcards for use in authentication.

This method checks attempts to ensure that the each of the nominated smartcards is available and prepared for use. This may result in interactive requests for pin confirmation, depending on the card.

Returns

Returns True if at least one smartcard was activated, and False otherwise.

Return type bool

read_only

Whether this filesystem client should be permitted to attempt any write operations.

Type bool

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to duct.disconnect().connect().

Returns A reference to this object.

Return type Duct instance

remove (*path*, *recursive=False*)

Remove file(s) at a nominated path.

Directories (and their contents) will not be removed unless recursive is set to True.

Parameters

- **path** (*str*) The path of the file/directory to be removed.
- **recursive** (bool) Whether to remove directories and all of their contents.

reset()

Reset this *Duct* instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type Duct instance

show_port_forwards()

Print to stdout the active port forwards associated with this client.

showdir(path=None)

Return a dataframe representation of a directory.

This method returns a *pandas.DataFrame* representation of the contents of a path, which are retrieved using *.dir(path)*. The exact columns will vary from filesystem to filesystem, depending on the fields returned by *.dir()*, but the returned DataFrame is guaranteed to at least have the columns: 'name' and 'type'.

Parameters path (*str*) – The path of the directory from which to show contents.

Returns A DataFrame representation of the contents of the nominated directory.

Return type pandas.DataFrame

upload (*source*, *dest=None*, *overwrite=False*, *fs=None*)

Upload files from another filesystem.

This method (recursively) uploads a file/folder from path *source* on filesystem *fs* to the path *dest* on this filesystem, overwriting any existing file if *overwrite* is *True*. This is equivalent to *fs.download*(..., *fs=self*).

Parameters

- **source** (str) The path on the specified filesystem (*fs*) of the file to upload to this filesystem. If *source* ends with '/', and corresponds to a directory, the contents of source will be copied instead of copying the entire folder.
- **dest** (str) The destination path on this filesystem. If not specified, the file/folder is uploaded into the default path, usually one's home folder, on this filesystem. If *dest* ends with '/' then file will be copied into destination folder, and will throw an error if path does not resolve to a directory.
- **overwrite** (*bool*) *True* if the contents of any existing file by the same name should be overwritten, *False* otherwise.
- **fs** (FileSystemClient) The FileSystemClient from which to load the file/folder at *source*. If not specified, defaults to the local filesystem.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided, then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '*<username>*'.

Type str

walk (path=None)

Explore the filesystem tree starting at a nominated path.

This method returns a generator which recursively walks over all paths that are children of *path*, one result for each directory, of form: (path name>, [<directory 1>, ...], [<file 1>, ...])

- **Parameters** path (*str*) The path of the directory from which to enumerate contents.
- **Returns** A generator of tuples, each tuple being associated with one directory that is either *path* or one of its descendants.

Return type generator<tuple>

5.5 Caches

All remote clients are expected to be subclasses of *Cache*, and so will share a common API. Protocol implementations are also free to add extra methods, which are documented in the "Subclass Reference" section below.

5.5.1 Common API

Wrap a method of a Duct class and add caching capabilities.

All arguments of this function are expected to be functions taking two arguments: a reference to current instance of the class (*self*) and a dictionary of arguments passed to the function (*kwargs*).

Parameters

- **key** (function -> str) The key under which the value returned by the wrapped function should be stored.
- **namespace** (function -> str) The namespace under which the key should be stored (default: "<duct class name>.<duct instance name>").
- **cache** (*function* -> *Cache*) The instance of cache via which to store the output of the wrapped function (default: *self.cache*).
- **use_cache** (function -> bool) Whether or not to use the caching functionality (default: *True*).
- **renew** (function -> bool) Whether to renew the stored cache, overriding if a value has already been stored (default: *False*).
- **serializer** (function -> Serializer) The Serializer subclass to use when storing the return object (default: *PickleSerializer*).
- **metadata** (function -> None, dict) A dictionary of additional metadata to be stored alongside the wrapped function's output (default: *None*).

Returns

The (potentially cached) object returned when calling the wrapped function.

Return type object

Raises Exception – If cache fails to store the output of the wrapped function, and the omniduct configuration key *cache_fail_hard* is *True*, then the underlying exceptions raised by the Cache instance will be reraised.

class omniduct.caches.base.Cache(**kwargs)

Bases: omniduct.duct.Duct

An abstract class providing the common API for all cache clients.

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- **port (int): The port number of the service (will be the port-forwarded** local port, if relevant; for remote port use ._*port*).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.

- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.
- prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

___init___(**kwargs)

- protocol (str, None): Name of protocol (used by Duct registries to inform Duct instances of how they were instantiated).
- name (str, None): The name to used by the Duct instance (defaults to class name if not specified).
- **registry** (DuctRegistry, None): The registry to use to lookup remote and/or cache instance specified by name.
- remote (str, RemoteClient): The remote by which the ducted service should be contacted.

host (str): The hostname of the service to be used by this client. port (int): The port of the service to be used by this client. username (str, bool, None): The username to authenticate with if necessary.

If True, then users will be prompted at runtime for credentials.

- **password (str, bool, None): The password to authenticate with if necessary.** If True, then users will be prompted at runtime for credentials.
- cache(Cache, None): The cache client to be attached to this instance. Cache will only used by specific methods as configured by the client.

cache_namespace(str, None): The namespace to use by default when writing to the cache.

set (key, value, namespace=None, serializer=None, metadata=None)
Set the value of a key.

Parameters

- **key** (*str*) The key for which *value* should be stored.
- **value** (*object*) The value to be stored.
- **namespace** (*str*, *None*) The namespace to be used.
- **serializer** (*Serializer*) The *Serializer* subclass to use for the serialisation of value into the cache. (default=PickleSerializer)
- **metadata** (*dict*, *None*) Additional metadata to be stored with the value in the cache. Values must be serializable via *yaml.safe_dump*.

```
set_metadata (key, metadata, namespace=None, replace=False)
Set the metadata associated with a stored key, creating the key if it is missing.
```

Parameters

- **key** (*str*) The key for which *value* should be stored.
- **metadata** (*dict*, *None*) Additional/override metadata to be stored for *key* in the cache. Values must be serializable via *yaml.safe_dump*.
- **namespace** (*str*, *None*) The namespace to be used.
- **replace** (*bool*) Whether the provided metadata should entirely replace any existing metadata, or just update it. (default=False)

get (*key*, *namespace=None*, *serializer=None*)

Retrieve the value associated with the nominated key from the cache.

Parameters

- **key** (*str*) The key for which *value* should be retrieved.
- **namespace** (*str*, *None*) The namespace to be used.
- **serializer** (*Serializer*) The *Serializer* subclass to use for the deserialisation of value from the cache. (default=PickleSerializer)

Returns The (appropriately deserialized) object stored in the cache.

Return type object

get_bytecount (key, namespace=None)

Retrieve the number of bytes used by a stored key.

This bytecount may or may not include metadata storage, depending on the backend.

Parameters

- key(str) The key for which to extract the bytecount.
- namespace (*str*, *None*) The namespace to be used.

Returns

The number of bytes used by the stored value associated with the nominated key and namespace.

Return type int

get_metadata (key, namespace=None)

Retrieve metadata associated with the nominated key from the cache.

Parameters

- key(str) The key for which to extract metadata.
- **namespace** (*str*, *None*) The namespace to be used.

Returns The metadata associated with this namespace and key.

Return type dict

unset (key, namespace=None)

Remove the nominated key from the cache.

Parameters

• **key** (*str*) – The key which should be unset.

• **namespace** (*str*, *None*) – The namespace to be used.

unset_namespace (namespace=None)

Remove an entire namespace from the cache.

Parameters namespace (*str*, *None*) – The namespace to be removed.

namespaces

A list of the namespaces stored in the cache.

Type list <str,None>

has_namespace(namespace=None)

Check whether the cache has the nominated namespace.

Parameters namespace (str, None) - The namespace for which to check for existence.

Returns Whether the cache has the nominated namespaces.

Return type bool

keys (namespace=None)

Collect a list of all the keys present in the nominated namespaces.

Parameters namespace (*str*, *None*) – The namespace from which to extract all of the keys.

Returns The keys stored in the cache for the nominated namespace.

Return type list<str>

has_key(*key*, *namespace=None*)

Check whether the cache as a nominated key.

Parameters

- key(str) The key for which to check existence.
- **namespace** (*str*, *None*) The namespace from which to extract all of the keys.

Returns

Whether the cache has a value for the nominated namespace and key.

Return type bool

get_total_bytecount (namespaces=None)

Retrieve the total number of bytes used by the cache.

This method iterates over all (nominated) namespaces and the keys therein, summing the result of $.get_bytecount(...)$ on each.

Parameters namespaces (*list<str*, *None>*) – The namespaces to which the bytecount should be restricted.

Returns The total number of bytes used by the nominated namespaces.

Return type int

describe (namespaces=None)

Return a pandas DataFrame showing all keys and their metadata.

Parameters namespaces (*list<str*, *None>*) – The namespaces to which the summary should be restricted.

Returns

A representation of keys in the cache. Will include at least the following columns: ['bytes', 'namespace', 'key', 'created', 'last_accessed']. Any additional metadata for keys will be appended to these columns.

Return type pandas.DataFrame

prune (*namespaces=None*, *max_age=None*, *max_bytes=None*, *total_bytes=None*, *total_count=None*) Remove keys from the cache in order to satisfy nominated constraints.

Parameters

- namespaces (list<str, None>) The namespaces to consider for pruning.
- max_age (None, int, timedelta, relativedelta, date, datetime) - The number of days, a timedelta, or a relativedelta, indicating the maximum age of items in the cache (based on last accessed date). Deltas are expected to be positive.
- **max_bytes** (*None*, *int*) The maximum number of bytes for *each* key, allowing the pruning of larger keys.
- total_bytes (*None*, *int*) The total number of bytes for the entire cache. Keys will be removed from least recently accessed to most recently accessed until the constraint is satisfied. This constraint will be applied after max_age and max_bytes.
- total_count (*None*, *int*) The maximum number of items to keep in the cache. Keys will be removed from least recently accessed to most recently accessed until the constraint is satisfied. This constraint will be applied after max_age and max_bytes.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type *Duct* instance

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type *Duct* instance

is_connected()

Check whether this *Duct* instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

Cache Quirks: This method may be overridden by subclasses, but provides the following default behaviour:

- Ensures self.registry, self.remote and self.cache values are instances of the right types.
- It replaces string values of *self.remote* and *self.cache* with remotes and caches looked up using *self.registry.lookup*.
- It looks through each of the fields nominated in *self.prepared_fields* and, if the corresponding value is callable, sets the value of that field to result of calling that value with a reference to *self*. By default, *prepared_fields* contains '_host', '_port', '_username', and '_password'.
- Ensures value of self.port is an integer (or None).

5.5.2 Subclass Reference

For comprehensive documentation on any particular subclass, please refer to one of the below documents.

FileSystemCache

class omniduct.caches.filesystem.FileSystemCache(**kwargs)
 Bases: omniduct.caches.base.Cache

An implementation of Cache that wraps around a FilesystemClient.

Attributes inherited from Duct:

- **protocol (str): The name of the protocol for which this instance was** created (especially useful if a *Duct* subclass supports multiple protocols).
- name (str): The name given to this Duct instance (defaults to class name).
- host (str): The host name providing the service (will be '127.0.0.1', if service is port forwarded from remote; use ._host to see remote host).
- port (int): The port number of the service (will be the port-forwarded local port, if relevant; for remote port use ._port).

username (str, bool): The username to use for the service. password (str, bool): The password to use for the service. registry (None, omniduct.registry.DuctRegistry): A reference to a

DuctRegistry instance for runtime lookup of other services.

- **remote (None, omniduct.remotes.base.RemoteClient): A reference to a** *RemoteClient* instance to manage connections to remote services.
- cache (None, omniduct.caches.base.Cache): A reference to a *Cache* instance to add support for caching, if applicable.
- **connection_fields (tuple<str>, list<str>):** A list of instance attributes to monitor for changes, whereupon the *Duct* instance should automatically disconnect. By default, the following attributes are monitored: 'host', 'port', 'remote', 'username', and 'password'.

prepared_fields (tuple<str>, list<str>): A list of instance attributes to be populated (if their values are callable) when the instance first connects to a service. Refer to *Duct.prepare* and *Duct._prepare* for more details. By default, the following attributes are prepared: '_host', '_port', '_username', and '_password'.

Additional attributes including host, port, username and password are documented inline.

Class Attributes:

- AUTO_LOGGING_SCOPE (bool): Whether this class should be used by omniduct logging code as a "scope". Should be overridden by subclasses as appropriate.
- **DUCT_TYPE (Duct.Type): The type of** *Duct* **service that is provided by** this Duct instance. Should be overridden by subclasses as appropriate.
- **PROTOCOLS (list<str>):** The name(s) of any protocols that should be associated with this class. Should be overridden by subclasses as appropriate.

class Type

Bases: enum.Enum

The *Duct.Type* enum specifies all of the permissible values of *Duct.DUCT_TYPE*. Also determines the order in which ducts are loaded by DuctRegistry.

__init__(**kwargs)

- protocol (str, None): Name of protocol (used by Duct registries to inform Duct instances of how they were instantiated).
- name (str, None): The name to used by the Duct instance (defaults to class name if not specified).
- **registry** (DuctRegistry, None): The registry to use to lookup remote and/or cache instance specified by name.
- remote (str, RemoteClient): The remote by which the ducted service should be contacted.

host (str): The hostname of the service to be used by this client. port (int): The port of the service to be used by this client. username (str, bool, None): The username to authenticate with if necessary.

If True, then users will be prompted at runtime for credentials.

- **password (str, bool, None): The password to authenticate with if necessary.** If True, then users will be prompted at runtime for credentials.
- cache(Cache, None): The cache client to be attached to this instance. Cache will only used by specific methods as configured by the client.

cache_namespace(str, None): The namespace to use by default when writing to the cache.

connect()

Connect to the service backing this client.

It is not normally necessary for a user to manually call this function, since when a connection is required, it is automatically created.

Returns A reference to the current object.

Return type Duct instance

describe (namespaces=None)

Return a pandas DataFrame showing all keys and their metadata.

Parameters namespaces (*list<str*, *None>*) – The namespaces to which the summary should be restricted.

Returns

A representation of keys in the cache. Will include at least the following columns: ['bytes', 'namespace', 'key', 'created', 'last_accessed']. Any additional metadata for keys will be appended to these columns.

Return type pandas.DataFrame

disconnect()

Disconnect this client from backing service.

This method is automatically called during reconnections and/or at Python interpreter shutdown. It first calls *Duct._disconnect* (which should be implemented by subclasses) and then notifies the *RemoteClient* subclass, if present, to stop port-forwarding the remote service.

Returns A reference to this object.

Return type Duct instance

classmethod for_protocol(protocol)

Retrieve a Duct subclass for a given protocol.

Parameters protocol (*str*) – The protocol of interest.

Returns

The appropriate class for the provided, partially constructed with the *protocol* keyword argument set appropriately.

Return type functools.partial object

Raises DuctProtocolUnknown – If no class has been defined that offers the named protocol.

get (key, namespace=None, serializer=None)

Retrieve the value associated with the nominated key from the cache.

Parameters

- **key** (*str*) The key for which *value* should be retrieved.
- **namespace** (*str*, *None*) The namespace to be used.
- **serializer** (*Serializer*) The *Serializer* subclass to use for the deserialisation of value from the cache. (default=PickleSerializer)

Returns The (appropriately deserialized) object stored in the cache.

Return type object

get_bytecount (key, namespace=None)

Retrieve the number of bytes used by a stored key.

This bytecount may or may not include metadata storage, depending on the backend.

Parameters

- **key** (*str*) The key for which to extract the bytecount.
- **namespace** (*str*, *None*) The namespace to be used.

Returns

The number of bytes used by the stored value associated with the nominated key and namespace.

Return type int

get_metadata (key, namespace=None)

Retrieve metadata associated with the nominated key from the cache.

Parameters

- key (*str*) The key for which to extract metadata.
- **namespace** (*str*, *None*) The namespace to be used.

Returns The metadata associated with this namespace and key.

Return type dict

get_total_bytecount (namespaces=None)

Retrieve the total number of bytes used by the cache.

This method iterates over all (nominated) namespaces and the keys therein, summing the result of .get_bytecount(...) on each.

Parameters namespaces (*list<str*, *None>*) – The namespaces to which the bytecount should be restricted.

Returns The total number of bytes used by the nominated namespaces.

Return type int

has_key(key, namespace=None)

Check whether the cache as a nominated key.

Parameters

- **key** (*str*) The key for which to check existence.
- **namespace** (*str*, *None*) The namespace from which to extract all of the keys.

Returns

Whether the cache has a value for the nominated namespace and key.

Return type bool

has_namespace(namespace=None)

Check whether the cache has the nominated namespace.

Parameters namespace (*str*, *None*) – The namespace for which to check for existence.

Returns Whether the cache has the nominated namespaces.

Return type bool

host

The host name providing the service, or '127.0.0.1' if *self.remote* is not *None*, whereupon the service will be port-forwarded locally. You can view the remote hostname using *duct._host*, and change the remote host at runtime using: *duct.host* = '<*host*>'.

Type str

is_connected()

Check whether this Duct instances is currently connected.

This method checks to see whether a *Duct* instance is currently connected. This is performed by verifying that the remote host and port are still accessible, and then by calling *Duct._is_connected*, which should be implemented by subclasses.

Returns Whether this *Duct* instance is currently connected.

Return type bool

keys (namespace=None)

Collect a list of all the keys present in the nominated namespaces.

Parameters namespace (*str*, *None*) – The namespace from which to extract all of the keys.

Returns The keys stored in the cache for the nominated namespace.

Return type list<str>

namespaces

A list of the namespaces stored in the cache.

Type list <str,None>

password

Some services require authentication in order to connect to the service, in which case the appropriate password can be specified. If *True* was provided at instantiation, you will be prompted to type your password at runtime when necessary. If *False* was provided, then *None* will be returned. You can specify a different password at runtime using: *duct.password* = '*<password*>'.

Type str

port

The local port for the service. If *self.remote* is not *None*, the port will be port-forwarded from the remote host. To see the port used on the remote host refer to *duct._port*. You can change the remote port at runtime using: duct.port = < port >.

Type int

prepare()

Prepare a Duct subclass for use (if not already prepared).

This method is called before the value of any of the fields referenced in *self.connection_fields* are retrieved. The fields include, by default: 'host', 'port', 'remote', 'cache', 'username', and 'password'. Subclasses may add or subtract from these special fields.

When called, it first checks whether the instance has already been prepared, and if not calls *_prepare* and then records that the instance has been successfully prepared.

prune (*namespaces=None*, *max_age=None*, *max_bytes=None*, *total_bytes=None*, *total_count=None*) Remove keys from the cache in order to satisfy nominated constraints.

Parameters

- namespaces (list<str, None>) The namespaces to consider for pruning.
- max_age (None, int, timedelta, relativedelta, date, datetime) - The number of days, a timedelta, or a relativedelta, indicating the maximum age of items in the cache (based on last accessed date). Deltas are expected to be positive.
- **max_bytes** (*None*, *int*) The maximum number of bytes for *each* key, allowing the pruning of larger keys.
- total_bytes (*None*, *int*) The total number of bytes for the entire cache. Keys will be removed from least recently accessed to most recently accessed until the constraint is satisfied. This constraint will be applied after max_age and max_bytes.
- total_count (*None*, *int*) The maximum number of items to keep in the cache. Keys will be removed from least recently accessed to most recently accessed until the constraint is satisfied. This constraint will be applied after max_age and max_bytes.

reconnect()

Disconnects, and then reconnects, this client.

Note: This is equivalent to *duct.disconnect().connect()*.

Returns A reference to this object.

Return type *Duct* instance

reset()

Reset this Duct instance to its pre-preparation state.

This method disconnects from the service, resets any temporary authentication and restores the values of the attributes listed in *prepared_fields* to their values as of when *Duct.prepare* was called.

Returns A reference to this object.

Return type *Duct* instance

set (key, value, namespace=None, serializer=None, metadata=None)

Set the value of a key.

Parameters

- **key** (*str*) The key for which *value* should be stored.
- **value** (*object*) The value to be stored.
- **namespace** (*str*, *None*) The namespace to be used.
- **serializer** (*Serializer*) The *Serializer* subclass to use for the serialisation of value into the cache. (default=PickleSerializer)
- **metadata** (*dict*, *None*) Additional metadata to be stored with the value in the cache. Values must be serializable via *yaml.safe_dump*.

set_metadata (key, metadata, namespace=None, replace=False)

Set the metadata associated with a stored key, creating the key if it is missing.

Parameters

- **key** (*str*) The key for which *value* should be stored.
- **metadata** (*dict*, *None*) Additional/override metadata to be stored for *key* in the cache. Values must be serializable via *yaml.safe_dump*.
- namespace (*str*, *None*) The namespace to be used.
- **replace** (*bool*) Whether the provided metadata should entirely replace any existing metadata, or just update it. (default=False)

unset (key, namespace=None)

Remove the nominated key from the cache.

Parameters

- **key** (*str*) The key which should be unset.
- **namespace** (*str*, *None*) The namespace to be used.

unset_namespace (namespace=None)

Remove an entire namespace from the cache.

Parameters namespace (*str*, *None*) – The namespace to be removed.

username

Some services require authentication in order to connect to the service, in which case the appropriate username can be specified. If not specified at instantiation, your local login name will be used. If *True* was provided, you will be prompted to type your username at runtime as necessary. If *False* was provided,

then *None* will be returned. You can specify a different username at runtime using: *duct.username* = '<*username*>'.

Type str

5.6 Registry Management

Omniduct provides some simple tooling to help manage ensembles of *Duct* configurations. The primary tool is the *DuctRegistry*, which manages *Duct* instances and allows them to communicate with each other.

For some simple examples on its use, please refer to the Quickstart.

```
class omniduct.registry.DuctRegistry(config=None)
    Bases: object
```

A convenient registry for Duct instances.

This class provides a simple interface to a pool of configured services, allowing convenient lookups of available services and the creation of new ones. It also allows for the batch creation of services from a shared configuration, which is especially useful in a company deployment.

___init___(config=None)

```
Parameters config (iterable, dict, str, None) – Refer to .import_from_config for more details (default: None).
```

register (*duct*, *name=None*, *override=False*, *register_magics=True*) Register an existing Duct instance into the registry.

Names of ducts can consist of any valid Python identifier, and multiple names can be provided as a comma separated list in which case the names will be aliases referring to the same *Duct* instance. Keep in mind that any name must uniquely identify one *Duct* instance.

Parameters

- duct (Duct) The Duct instance to be registered.
- **name** (*str*) An optional name to use when registering. If not provided this will fall back to *duct.name*. If neither is configured, an error will be thrown. Name can be a comma-separated list of names, in which case the names are aliases and will point to the same *Duct* instance.
- **override** (*bool*) Whether to override any existing *Duct* instance of the same name. If *False*, any overrides will result in an exception.

Returns The *Duct* instance being registered.

Return type Duct

new (*name*, *protocol*, *override=False*, *register_magics=True*, ***kwargs*) Create a new service and register it into the registry.

Parameters

- **name** (*str*) The name (or names) of the target service. If multiple aliases are to be used, names should be a comma separated list. See *.register* for more details.
- **protocol** (*str*) The protocol of the new service.
- **override** (bool) Whether to override any existing *Duct* instance of the same name. If *False*, any overrides will result in an exception.

- **register_magics** (*bool*) Whether to register the magics if running in and IPython session (default: *True*).
- ****kwargs** (*dict*) Additional arguments to pass to the constructor of the class associated with the nominated protocol.

Returns The *Duct* instance registered into the registry.

Return type Duct

names

The names of all ducts in the registry.

Type list

lookup (name, kind=None)

Look up an existing registered Duct by name and (optionally) kind.

Parameters

- **name** (*str*) The name of the *Duct* instance.
- kind (str, Duct.Type) The kind of Duct to which the lookup should be restricted.

Returns The looked up *Duct* instance.

Return type Duct

Raises DuctNotFound - If no Duct can be found for requested name and/or type.

populate_namespace (namespace=None, names=None, kinds=None)

Populate a nominated namespace with references to a subset of ducts.

While a registry object is a great way to store and configure *Duct* instances, it is sometimes desirable to surface frequently used instances in other more convenient namespaces (such as the globals of your module).

Parameters

- **namespace** (*dict*, *None*) The namespace to populate. If using from a module you can pass globals(). If None, a new dictionary is created, populated and then returned.
- **names** (*list*<*str*>, *None*) The names to include in the population. If not specified then all names will be exported.
- **kinds** (*list*<*str*>, *None*) The kinds of ducts to include in the population. If not specified, all kinds will be exported.

Returns The populated namespace.

Return type dict

get_proxy(by_kind=True)

Return a structured proxy object for easy exploration of services.

This method returns a proxy object to the registry upon which the *Duct* instances are available as attributes. This object is also by default structured such that one first accesses an attribute associated with a kind, which makes larger collections of services more easily navigatable.

For example, if you have *DatabaseClient* subclass registered as 'my_service', you could access it on the proxy using: >>> proxy = registry.get_proxy(by_kind=True) >>> proxy.databases.my_service

Parameters by_kind (bool) – Whether to nest proxy of Duct instances by kind.

Returns The proxy object.

Return type ServicesProxy

register_from_config (config, override=False)

Register a collection of Duct service configurations.

The configuration format must be one of the following: - An iterable sequence of dictionaries containing a mapping between the

keyword arguments required to instantiate the Duct subclass.

- A dictionary mapping names of *Duct* instances to dictionaries of keyword arguments.
- A dictionary mapping Duct types ('databases', 'filesystems', etc) to mappings like those immediately above.
- A string YAML representation of one of the above (with at least one newline character).
- A string filename containing such a YAML representation.

There are three special keyword arguments that are required by the *DuctRegistry* instance: - name: Should be present only in the configuration dictionary when

config is provided as an iterable sequence of dictionaries.

- protocol: Which specifies which *Duct* subclass to fetch. Failure to correctly set this will result in a warning and an ignoring of this configuration.
- register_magics (optional): A boolean flag indicating whether to register any magics defined by this Duct class (default: True).

Parameters

- **config** (*iterable*, *dict*, *str*, *None*) A configuration specified in one of the above described formats.
- **override** (bool) Whether to override any existing *Duct* instance of the same name(s). If *False*, any overrides will result in an exception.

Omniduct's API has been designed to ensure that ducts which provide the same type of service (i.e. database querying, filesystem grokking, etc) also provide a programmatically similar API. As such, all protocol implementations are subclasses of a generic abstract class *Duct* via a protocol type-specific subclass (such as *DatabaseClient* for database protocols). This ensures that the core API is consistent between all instances of the same protocol type. These type-specific classes may also derive from *omniduct.utils.magics.MagicsProvider*, and provide IPython magic functions to provide convenient access to these protocols in IPython sessions. Protocol implementations can also have protocol-specific additions to the core API.

The *Duct* class provides the scaffolding for connection management and other "magic" such as the automatic creation of a registry of the protocols handled by subclasses. This class is described in more detail in *Core Classes*, along with the *MagicsProvider* class.

The protocol-specific subclasses of *Duct* that provide the shared APIs (including any IPython magics) for each protocol type are detailed in dedicated pages; i.e. *Databases*, *Filesystems*, *Remotes*, and *Caches*.

Lastly, utility classes and methods are provided to help manage registries of connections to various services. These are documented in *Registry Management*.

Note Omniduct does not guarantee a stable API between major versions. However, we do commit to ensuring that version x.y.z of *omniduct* is API forward-compatible with all future minor versions x.y.*. While there is no guarantee of APIs remaining fixed between major versions, we expect that in practice these breaking API changes will be small, and in all cases will be documented in the release notes. As such, if you are using Omniduct in a production environment, we recommend

installing using a static pinned version or something like *omniduct>=1.2.3<1.3*, where 1.2.3 is the version found to work well in your environment.

CHAPTER 6

Extensions and Plug-ins

Extending Omniduct to support additional services is relatively straightforward, requiring you only to subclass *Duct* or one of the protocol specific common API subclasses (a template for each of these is provided as a *stub.py* file in the appropriate subpackage, e.g. https://github.com/airbnb/omniduct/blob/master/omniduct/databases/stub.py).

As soon as your subclass is in memory, it will integrate automatically with the rest of the Omniduct ecosystem, and be instantiatable by protocol name through the *DuctRegistry* or *Duct.for_protocol()* systems.

If you would like to contribute this extension into the upstream Omniduct library, we welcome your contribution. This would entail simply adding a module containing your subclass to the appropriate Omniduct subpackage, and then (if it is stable and ready for broad usage) importing that subpackage from *omniduct.protocols*. Once your module is merged into the master branch of Omniduct, maintainance will fall to the core Omniduct maintainers, though you are of course welcome to continue submitting patches to improve it or any other aspect of Omniduct.

If you need further assistance, please do not hesitate to open an issue on our issue tracker: https://github.com/airbnb/ omniduct/issues.

CHAPTER 7

Contributions

Contributions of any nature are welcome, including software patches, improvements to documentation, bug reports, or feature requests. One of the most useful contributions will undoubtedly be support for new protocols, and so we look forward to seeing your patches to support your favourite services.

For documentation on how to contribute support for new protocols, please refer to Extensions and Plug-ins.

Omniduct is an extensible Python library that provides uniform interfaces to a wide variety of (potentially) remote data providers such as databases, filesystems, and REST services. Its primary objective is to simplify the process of collecting and analysing data in a heterogeneous data environment, and is suitable for deployment in interactive and production environments. To that end, it offers the following features:

- A generic plugin-based programmatic API to access data in a consistent manner across different services (see *Supported protocols*).
- A framework for lazily connecting to data sources and maintaining these connections during the entire lifetime of the relevant Python session.
- Automatic port forwarding of remote services over SSH where connections cannot be made directly.
- Convenient IPython magic functions for interfacing with data providers from within IPython and Jupyter Notebook sessions.
- Utility classes and methods to assist in maintaining registries of useful services.

Omniduct has been designed such that it is convenient to use directly (each user can configure their own service definitions) or via another package (which can create a library of pre-defined services, such as for a company). For more information on how to deploy *omniduct* refer to *Deployment*.

CHAPTER $\mathbf{8}$

Indices and tables

- genindex
- modindex
- search

Python Module Index

0

omniduct.caches.base,144
omniduct.filesystems.base,90
omniduct.registry,156

Index

Symbols	С
init() (omniduct.caches.base.Cache method),	Cache (class in omniduct.caches.base), 145
146	<pre>cached_method() (in module omniduct.caches.base),</pre>
init() (omniduct.caches.filesystem.FileSystemCac	<i>he</i> 144
<i>method</i>), 151	connect() (<i>omniduct.caches.base.Cache method</i>), 149
init() (omniduct.databases.base.DatabaseClient	<pre>connect() (omniduct.caches.filesystem.FileSystemCache</pre>
method), 16	<i>method</i>), 151
init() (omniduct.databases.druid.DruidClient	connect() (<i>omniduct.databases.base.DatabaseClient</i>
method), 28	method), 23
init() (omniduct.databases.hiveserver2.HiveServer	er26hinmect() (omniduct.databases.druid.DruidClient
method), 38	method), 28
init() (omniduct.databases.neo4j.Neo4jClient	<pre>connect() (omniduct.databases.hiveserver2.HiveServer2Client</pre>
method), 49	method), 38
init() (omniduct.databases.presto.PrestoClient	<pre>connect() (omniduct.databases.neo4j.Neo4jClient</pre>
method), 60	method), 49
init() (omniduct.databases.pyspark.PySparkClier	<pre>ntconnect() (omniduct.databases.presto.PrestoClient</pre>
method), 70	method), 60
init() (omniduct.databases.sqlalchemy.SQLAlche	myGhienetct () (omniduct.databases.pyspark.PySparkClient
method), 81	method), 70
<pre>init() (omniduct.duct.Duct method), 12</pre>	connect() (<i>omniduct.databases.sqlalchemy.SQLAlchemyClient</i>
init() (omniduct.filesystems.base.FileSystemClien	nt method), 81
method), 91	connect() (<i>omniduct.duct.Duct method</i>), 14
<pre>init() (omniduct.filesystems.base.FileSystemFile</pre>	<pre>connect() (omniduct.filesystems.base.FileSystemClient</pre>
method), 96	method), 95
init() (omniduct.filesystems.local.LocalFsClient	connect() (<i>omniduct.filesystems.local.LocalFsClient</i>
method), 98	method), 98
init() (<i>omniduct.filesystems.s3.S3Client</i>	<pre>connect() (omniduct.filesystems.s3.S3Client method),</pre>
<i>method</i>), 105	105
init() (omniduct.filesystems.webhdfs.WebHdfsClie	entonnect()(omniduct.filesystems.webhdfs.WebHdfsClient
<i>method</i>), 112	<i>method</i>), 112
<pre>init() (omniduct.registry.DuctRegistry method),</pre>	<pre>connect() (omniduct.remotes.base.RemoteClient</pre>
156	method), 120
init() (omniduct.remotes.base.RemoteClient	<pre>connect() (omniduct.remotes.ssh.SSHClient method),</pre>
<i>method</i>), 119	126
init() (omniduct.remotes.ssh.SSHClient	<pre>connect() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient</pre>
<i>method</i>), 126	<i>method</i>), 136
init() (omniduct.remotes.ssh_paramiko.Paramiko	SSHClient
<i>method</i>), 136	U
_prepare() (<i>omniduct.duct.Duct method</i>), 13	DatabaseClient (class in omniduct.databases.base),

15	50
<pre>dataframe_to_table() (om-</pre>	disconnect() (om-
niduct.databases.base.DatabaseClient	niduct.databases.presto.PrestoClient method),
<i>method</i>), 21	60
<pre>dataframe_to_table() (om-</pre>	disconnect() (om-
niduct.databases.druid.DruidClient method), 28	niduct.databases.pyspark.PySparkClient method), 71
<pre>dataframe_to_table() (om-</pre>	disconnect() (om-
niduct.databases.hiveserver2.HiveServer2Client method), 39	niduct.databases.sqlalchemy.SQLAlchemyClient method), 81
<pre>dataframe_to_table() (om-</pre>	disconnect() (<i>omniduct.duct.Duct method</i>), 14
niduct.databases.neo4j.Neo4jClient method), 50	disconnect() (om- niduct.filesystems.base.FileSystemClient
<pre>dataframe_to_table() (om-</pre>	method), 96
niduct.databases.presto.PrestoClient method),	disconnect() (om-
60 dataframe to table() (om-	niduct.filesystems.local.LocalFsClient method), 98
niduct.databases.pvspark.PvSparkClient	disconnect() (omniduct.filesystems.s3.S3Client
method), 71	<i>method</i>), 105
<pre>dataframe_to_table() (om-</pre>	disconnect() (om-
niduct.databases.sqlalchemy.SQLAlchemyClient method), 81	niduct.filesystems.webhdfs.WebHdfsClient method), 113
describe() (omniduct.caches.base.Cache method),	disconnect() (omniduct.remotes.base.RemoteClient
148	<i>method</i>), 122
<pre>describe() (omniduct.caches.filesystem.FileSystemCach</pre>	heisconnect() (omniduct.remotes.ssh.SSHClient
method), 151	<i>method</i>), 127
dir() (omniduct.filesystems.base.FileSystemClient	disconnect() (om-
method), 93	niduct.remotes.ssh_paramiko.ParamikoSSHClient
dir() (omniduct.filesystems.local.LocalFsClient	method), 137
<i>method</i>), 98	download () (omniauci.filesystems.base.FilesystemClient
dir() (omnauci.juesystems.s5.55Cient method), 105 dir() (omniduct filesystems webbdfs WebHdfsClient	download() (omniduct filesystems local LocalEsClient
method), 112	method), 98
dir() (omniduct.remotes.base.RemoteClient method), 121	download() (omniduct.filesystems.s3.S3Client method), 106
dir() (omniduct.remotes.ssh.SSHClient method), 126	download() (omniduct.filesystems.webhdfs.WebHdfsClient
dir () (omniduct.remotes.ssh_paramiko.ParamikoSSHClie	ent method), 113
disconnect () (omniduct caches base Cache	download() (omniduct.remotes.base.RemoteClient method) 122
method). 149	download() (omniduct.remotes.ssh.SSHClient
disconnect() (om-	method), 127
niduct.caches.filesystem.FileSystemCache method), 152	<pre>download() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient method), 137</pre>
disconnect() (om-	DruidClient (class in omniduct.databases.druid), 27
niduct.databases.base.DatabaseClient	DruidClient.Type (class in om-
method), 23	niduct.databases.druid), 28
disconnect() (om-	Duct (class in omniduct.duct), 11
niduct.databases.druid.DruidClient method),	Duct.Type (class in omniduct.duct), 12
28	DuctRegistry (<i>class in omniduct.registry</i>), 156
disconnect() (om-	E C
niduct.databases.hiveserver2.HiveServer2Client	E
method), 40	execute() (omniduct.databases.base.DatabaseClient
niduct databases neo4i Neo4iClient method)	<i>method</i>), 17
munci.uunuuuuuuuuuuuuuuuuuuuuuuuuuuuuuuuu	

execute() (omniduct.databases.druid.DruidClient method), 28	execute_from_template() (om- niduct.databases.pyspark.PySparkClient
mathod) 40	2Client method), 72
(oppring to the control of the contr	miduct databases solalchemy SOL AlchemyClient
method) 50	mathed) 82
($($ $($ $))))) ($ $($ $)))))))))))))))))))$	exists () (omniduct filesystems have FileSystemClient
method) 61	method) 92
execute () (omniduct databases pyspark PySparkClient	exists() (omniduct filesystems local LocalFsClient
method). 71	method), 99
execute() (omniduct.databases.sglalchemy.SOLAlchem	we kienst s() (omniduct.filesystems.s3.S3Client method).
method), 81	106
execute() (<i>omniduct.remotes.base.RemoteClient</i>	exists() (omniduct.filesystems.webhdfs.WebHdfsClient
method), 120	<i>method</i>), 113
execute() (omniduct.remotes.ssh.SSHClient method), 128	<pre>exists() (omniduct.remotes.base.RemoteClient method), 122</pre>
execute() (omniduct.remotes.ssh_paramiko.ParamikoS	SHElistuts () (omniduct.remotes.ssh.SSHClient method),
<i>method</i>), 137	128
execute_from_file() (om-	<pre>exists() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient</pre>
niduct.databases.base.DatabaseClient	method), 137
method), 18	г
execute_from_file() (om-	F
niduct.databases.druid.DruidClient method),	FileSystemCache (class in om-
29	niduct.caches.filesystem), 150
execute_from_file() (om-	FileSystemCache.Type (class in om-
niauct.aatabases.niveserver2.HiveServer2Client	niduct.caches.filesystem), 151
meinoa), 40	FileSystemClient (class in om-
viduat databases needi NeediClient method	niduct.filesystems.base), 90
51	FileSystemFile (<i>Class in om-</i>
execute from file() (om-	Eilo Sust on Eilo Doog (alang in on
niduct databases presto PrestoClient method).	riduct flagstams hasa) 96
61	find() (omniduct filesystems have FileSystemClient
execute from file() (om-	method) 94
niduct.databases.pyspark.PySparkClient	find() (omniduct filesystems.local.LocalFsClient
method), 72	method), 99
execute_from_file() (om-	find() (omniduct.filesystems.s3.S3Client method), 106
niduct.databases.sqlalchemy.SQLAlchemyClient	find() (omniduct.filesystems.webhdfs.WebHdfsClient
method), 82	<i>method</i>), 113
execute_from_template() (om-	<pre>find() (omniduct.remotes.base.RemoteClient method),</pre>
niduct.databases.base.DatabaseClient	122
method), 20	<pre>find() (omniduct.remotes.ssh.SSHClient method), 128</pre>
execute_from_template() (om-	find() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient
niduct.databases.druid.DruidClient method),	method), 138
$\frac{29}{29}$	for_protocol() (om-
execute_irom_template() (0m-	niduct.caches.filesystem.FileSystemCache
method) 41	class method), 152
execute from template() (om-	IUI_PTOLOCOI() (0m-
niduct.databases.neo4i.Neo4iClient method)	manci.aaaooses.arma.DrmaCheni Class
51	$for protocol() \qquad (om-$
<pre>execute_from_template() (om-</pre>	niduct databases hiveserver? HiveServer?Client
niduct.databases.presto.PrestoClient method),	class method). 41
62	<i>"</i>

for_protocol()	(<i>om</i> -
niduct.databases.neo4j.Neo4jClient	class
<i>method</i>), 51	
for_protocol()	(<i>om</i> -
niduct.databases.presto.PrestoClient	class
method), 62	
for_protocol()	(<i>om</i> -
niduct.databases.pyspark.PySparkClient	
class method), 72	
for_protocol()	(<i>om</i> -
niduct.databases.sqlalchemy.SQLAlchem	yClient
class method), 82	
for_protocol() (omniduct.duct.Duct class me	thod),
13	
for_protocol()	(<i>om</i> -
niduct.filesystems.local.LocalFsClient	class
method), 99	
<pre>for_protocol() (omniduct.filesystems.s3.S3</pre>	Client
class method), 106	
for_protocol()	(<i>om</i> -
niduct.filesystems.webhdfs.WebHdfsClien	t
class method), 114	
<pre>for_protocol() (omniduct.remotes.ssh.SSH</pre>	Client
class method), 128	
for_protocol()	(<i>om</i> -
niduct.remotes.ssh_paramiko.ParamikoS	SHClie
class method), 138	

G

get() (omniduct.caches.base.Cache method), 147	ł
get () (omniduct.caches.filesystem.FileSystemCache	
method), 152	
get bytecount() (omniduct.caches.base.Cache	ł
method), 147	
get bytecount() (om-	ł
niduct.caches.filesvstem.FileSvstemCache	
method). 152	
get local uri() (om-	F
niduct remotes base RemoteClient method)	-
121	F
get local uni () (omniduct remotes sch SSHClient	. 1
get_iotai_uii() (ommunci.remotes.ssn.ssifettent	ł
memou), 129	1
get_10Ca1_ur1() (0m-	
niduct.remotes.ssn_paramiko.ParamikoSSHCile	<i>nt</i> r?
method), 138	
get_metadata() (<i>omniduct.caches.base.Cache</i>	ł
<i>method</i>), 147	
get_metadata() (om-	ł
niduct.caches.filesystem.FileSystemCache	
method), 152	ł
get proxy() (<i>omniduct.registry.DuctRegistry</i>)	
<i>method</i>), 157	ł
get total bytecount() (om-	
niduct caches base Cache method) 148	
maneneaches.cuse.cuche memouj, 110	

get_total_bytecount()	(om-
niduct.caches.filesystem.FileSystemCache	
method), 153	
global_writes	(<i>om</i> -
niduct.filesystems.base.FileSystemClient	
attribute), 92	
global_writes	(<i>om</i> -
niduct.filesystems.local.LocalFsClient	at-
tribute), 99	
global_writes (omniduct.filesystems.s3.S3Clie	ent at-
tribute), 107	
global_writes	(om-
niduct.filesystems.webhdfs.WebHdfsClient	t
attribute), 114	
global_writes (omniduct.remotes.ssh.SSHClie	nt at-
tribute), 129	
global_writes	(om-
niduct.remotes.ssh_paramiko.ParamikoSS	HClient
attribute), 138	
···	

Н

<pre>has_key() (omniduct.caches.base.Cache method), 148 has_key() (omniduct.caches.filesystem.FileSystemCache</pre>	
has_namespace() (omniduct.caches.base.Cache nt method), 148	
has_namespace() (om-	
niduct.caches.filesystem.FileSystemCache	
<i>method</i>), 153	
has_port_forward() (om-	
niduct.remotes.base.RemoteClient method), 121	
has_port_forward() (om-	
niduct.remotes.ssh.SSHClient method), 129	
has_port_forward() (om-	
niduct.remotes.ssh_paramiko.ParamikoSSHClient	1
method), 138	
HiveServer2Client (class in om-	
niduct.databases.hiveserver2), 37	
HiveServer2Client.Type (class in om-	
niduct.databases.hiveserver2), 38	
host (omniduct.caches.filesystem.FileSystemCache at-	
tribute), 153	
nthost (omniduct.databases.druid.DruidClient attribute),	
30	
host (omniduct.databases.hiveserver2.HiveServer2Client	
attribute), 41	
host (omniduct.databases.neo4j.Neo4jClient attribute),	
51	
host (omniduct.databases.presto.PrestoClient at-	
tribute), 62	
host (omniduct.databases.pyspark.PySparkClient at-	
tribute), 72	

host (omniduct.databases.sqlalchemy.SQLAlchemyClient	i
host (omniduct duct Duct attribute) 14	-
host (omniduct.duct.Duct attribute), 14	T :
tribute), 100	
host (omniduct.filesystems.s3.S3Client attribute), 107	i
host (omniduct.filesystems.webhdfs.WebHdfsClient at- tribute) 114	
host (omniduct remotes ssh SSHClient attribute) 129	i
host (omniduct remotes ssh paramiko ParamikoSSHClien	nt.
attribute) 139	i.
1	
<pre>is_connected() (omniduct.caches.base.Cache</pre>	i
<i>method</i>), 149	
is_connected() (om-	i
niduct.caches.filesystem.FileSystemCache	
<i>method</i>), 153	i
is_connected() (om-	
niduct.databases.base.DatabaseClient	i
method), 23	
is connected() (om-	i
<i>niduct.databases.druid.DruidClient</i> method).	
30	i
is connected() (om-	
niduct.databases.hiveserver2.HiveServer2Client	i
method). 41	
is connected() (om-	i
niduct.databases.neo4i.Neo4iClient_method).	
52	i
is connected() (om-	
niduct.databases.presto.PrestoClient_method).	i
62.	
is connected() (om-	i
niduct.databases.pvspark.PvSparkClient	
method), 72	i
is_connected() (om-	
niduct.databases.sqlalchemy.SQLAlchemyClient	T :
method), 83	4
is_connected() (omniduct.duct.Duct method), 14	Τŝ
is_connected() (om-	
niduct.filesystems.base.FileSystemClient	K
method), 96	,
is_connected() (<i>om</i> -	k e
niduct.filesystems.local.LocalFsClient	К¢
method), 100	
is_connected() (omniduct.filesystems.s3.S3Client	ı.
method), 107	L
is_connected() (om-	1:
niduct.filesystems.webhdfs.WebHdfsClient	
<i>method</i>), 114	1:
is_connected() (om-	
niduct.remotes.base.RemoteClient method),	1:
123	

is_connected() (<i>omniduct.remotes.ssh.SSHClient</i> method) 129
is connected() (om-
niduct.remotes.ssh paramiko.ParamikoSSHClient
method), 139
is port bound() (om-
niduct.remotes.base.RemoteClient method).
121
is_port_bound() (omniduct.remotes.ssh.SSHClient method) 129
is port hound() (or
niduct remotes ssh paramiko Paramiko SSHClient
mathed) 139
isdir() (omniduct.filesystems.base.FileSystemClient
method), 93
<pre>isdir() (omniduct.filesystems.local.LocalFsClient method), 100</pre>
isdir() (omniduct.filesystems.s3.S3Client method),
isdir() (omniduct.filesystems.webhdfs.WebHdfsClient method), 114
isdir() (omniduct.remotes.base.RemoteClient
method). 123
isdir() (omniduct.remotes.ssh.SSHClient method), 130
isdir() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient
i a fi la () (amniduat filosystems base FilosystemClient
method) 03
isfilo() (omniduct filesystems local LocalEsClient
method), 100
isfile() (omniduct.filesystems.s3.S3Client method),
107
<pre>isfile() (omniduct.filesystems.webhdfs.WebHdfsClient method), 114</pre>
isfile() (omniduct.remotes.base.RemoteClient
method), 123
<pre>isfile() (omniduct.remotes.ssh.SSHClient method),</pre>
<pre>isfile() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient</pre>
K
() (ampiduat agalas hass Casha method) 140
(omniauci.cucnes.ouse.cucne meinoa), 140
(omniauci.cacnes.juesystem.FileSystemCache method), 153
L
i at dir () (ampiduat filosystems have EileSystem Client
method), 93

Listdir() (omniduct.filesystems.s3.S3Client method), 107

<pre>listdir() (omniduct.filesystems.webhdfs.WebHdfsClien method), 115</pre>	tNAMESPACE_DEFAULTS_WRITE (om- niduct.databases.base.DatabaseClient at-
<pre>listdir() (omniduct.remotes.ssh.SSHClient method),</pre>	tribute), 16
130	NAMESPACE_DEFAULTS_WRITE (om-
<pre>listdir() (omniduct.remotes.ssh_paramiko.ParamikoSt method), 139</pre>	SHClient niduct.databases.druid.DruidClient attribute), 27
LocalFsClient (class in omniduct.filesystems.local),	NAMESPACE_DEFAULTS_WRITE (om-
97	niduct.databases.hiveserver2.HiveServer2Client
LocalFsClient.Type (class in om-	attribute), 38
niduct.filesystems.local), 98	NAMESPACE_DEFAULTS_WRITE (om-
lookup() (omniduct.registry.DuctRegistry method), 157	niduct.databases.neo4j.Neo4jClient attribute), 49
	NAMESPACE_DEFAULTS_WRITE (om-
M	niduct.databases.presto.PrestoClient attribute),
MagicsProvider (class in omniduct.utils.magics), 15	60
<pre>mkdir() (omniduct.filesystems.base.FileSystemClient</pre>	NAMESPACE_DEFAULTS_WRITE (om-
method), 94	niduct.databases.pyspark.PySparkClient
mkdir() (omniduct.filesystems.local.LocalFsClient	attribute), 70
<i>method</i>), 100	NAMESPACE_DEFAULTS_WRITE (om-
mkdir() (omniduct.filesystems.s3.S3Client method), 107	niduct.databases.sqlalchemy.SQLAlchemyClient attribute), 80
<pre>mkdir() (omniduct.filesystems.webhdfs.WebHdfsClient</pre>	namespaces (omniduct.caches.base.Cache attribute), 148
<pre>mkdir() (omniduct.remotes.base.RemoteClient method), 123</pre>	namespaces (omniduct.caches.filesystem.FileSystemCache attribute), 154
<pre>mkdir() (omniduct.remotes.ssh.SSHClient method), 130</pre>	Neo4jClient (<i>class in omniduct.databases.neo4j</i>), 48 Neo4jClient.Type (<i>class in om</i> -
<pre>mkdir() (omniduct.remotes.ssh_paramiko.ParamikoSSH method), 140</pre>	Client niduct.databases.neo4j), 49 new() (omniduct.registry.DuctRegistry method), 156
N	0
names (omniduct.registry.DuctRegistry attribute), 157	omniduct.caches.base(<i>module</i>),144
NAMESPACE_DEFAULTS_READ (om-	omniduct.filesystems.base(module),90
niduct.databases.base.DatabaseClient at-	omniduct.registry(module), 156

names (omni	duct.registry.l	DuctRegistry attribut	te), 157
NAMESPACE_	_DEFAULTS_	_READ	(<i>om</i> -
nidu	ct.databases.	base.DatabaseClien	t at-
tribi	<i>ute</i>), 16		
NAMESPACE	_DEFAULTS_	_READ	(<i>om</i> -
nidu	ct.databases.	druid.DruidClient d	attribute),
27			
NAMESPACE_	_DEFAULTS_	_READ	(om-
nidu	ct.databases.	hiveserver2.HiveSer	ver2Client
attri	bute), 38		
NAMESPACE_	_DEFAULTS_	_READ	(om-
nidu	ct.databases.	neo4j.Neo4jClient d	attribute),
49			
NAMESPACE_	_DEFAULTS_	_READ	(om-
nidu	ct.databases.	presto.PrestoClient d	attribute),
60			
NAMESPACE_	_DEFAULTS_	_READ	(om-
nidu	ct.databases.	pyspark.PySparkCli	ent
attri	bute), 70		
NAMESPACE_	_DEFAULTS_	_READ	(om-
nidu	ct.databases.	sqlalchemy.SQLAlch	nemyClient
attri	bute), 80		

open() (omniduct.filesystems.base.FileSystemClient method), 94 (omniduct.filesystems.local.LocalFsClientopen()

- *method*), 101
- open() (omniduct.filesystems.s3.S3Client method), 108
- open() (omniduct.filesystems.webhdfs.WebHdfsClient method), 115
- open() (omniduct.remotes.base.RemoteClient method), 123
- open() (omniduct.remotes.ssh.SSHClient method), 130
- open() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient method), 140

Ρ

- ParamikoSSHClient (class in omniduct.remotes.ssh_paramiko), 135 ParamikoSSHClient.Type (class in om
 - niduct.remotes.ssh_paramiko), 136
- password (omniduct.caches.filesystem.FileSystemCache attribute), 154

password (omniduct.databases.druid.DruidClient at- tribute) 30	<pre>path_dirname() (om- niduct filesystems local LocalEsClient</pre>
password (omniduct.databases.hiveserver2.HiveServer2	Client method), 101
attribute), 41	<pre>path_dirname() (omniduct.filesystems.s3.S3Client</pre>
password (omniduct.databases.neo4j.Neo4jClient at-	method), 108
tribute), 52	path_dirname() (<i>om</i> -
password (omniauci.aatabases.presto.PrestoClient at-	niauci, filesystems. webhajs. webHajsCiient
IFIDULE), 02	method), 110
attribute), 73	method), 131
password (omniduct.databases.sqlalchemy.SQLAlchemy	Chianth_dirname() (om-
attribute), 83	niduct.remotes.ssh_paramiko.ParamikoSSHClient
password (omniduct.duct.Duct attribute), 14	method), 141
password (omniduct.filesystems.local.LocalFsClient attribute), 101	path_home (omniduct.filesystems.base.FileSystemClient attribute), 91
password (omniduct.filesystems.s3.S3Client attribute),	<pre>path_home (omniduct.filesystems.local.LocalFsClient</pre>
108	attribute), 101
password (omniduct.filesystems.webhdfs.WebHdfsClient	path_home (omniduct.filesystems.s3.S3Client at-
attribute), 115	tribute), 108
password (omniduct.remotes.ssh.SSHClient attribute), 131	<pre>path_home (omniduct.filesystems.webhdfs.WebHdfsClient attribute), 116</pre>
password (omniduct.remotes.ssh_paramiko.ParamikoSSI	Helient_home (omniduct.remotes.base.RemoteClient at-
attribute), 140	tribute), 124
<pre>path_basename() (om-</pre>	path_home (omniduct.remotes.ssh.SSHClient at-
niduct.filesystems.base.FileSystemClient	tribute), 131
method), 92	path_home (omniduct.remotes.ssh_paramiko.ParamikoSSHClient
<pre>path_basename() (om-</pre>	attribute), 141
niduct.filesystems.local.LocalFsClient	<pre>path_join() (omniduct.filesystems.base.FileSystemClient</pre>
<i>method</i>), 101	method), 92
<pre>path_basename() (omniduct.filesystems.s3.S3Client method), 108</pre>	<pre>path_join() (omniduct.filesystems.local.LocalFsClient</pre>
path basename() (om-	path join() (omniduct.filesystems.s3.S3Client
niduct.filesystems.webhdfs.WebHdfsClient	<i>method</i>), 109
method), 115	<pre>path_join() (omniduct.filesystems.webhdfs.WebHdfsClient</pre>
<pre>path_basename() (omniduct.remotes.ssh.SSHClient</pre>	<i>method</i>), 116
<i>method</i>), 131	<pre>path_join() (omniduct.remotes.ssh.SSHClient</pre>
<pre>path_basename() (om-</pre>	<i>method</i>), 131
niduct.remotes.ssh_paramiko.ParamikoSSHClien	<pre>tpath_join() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient</pre>
<i>method</i>), 140	<i>method</i>), 141
<pre>path_cwd (omniduct.filesystems.base.FileSystemClient</pre>	path_normpath() (om-
attribute), 91	niduct.filesystems.base.FileSystemClient
path_cwd (omniduct.filesystems.local.LocalFsClient	method), 92
attribute), 101	path_normpath() (om-
<pre>path_cwd (omniduct.filesystems.s3.S3Client attribute),</pre>	niduct.filesystems.local.LocalFsClient method), 102
path_cwd (omniduct.filesystems.webhdfs.WebHdfsClient	path_normpath() (omniduct.filesystems.s3.S3Client
attribute), 116	method), 109
path_cwd (omniduct.remotes.ssh.SSHClient attribute),	path_normpath() (om-
	niduct.filesystems.webhafs.WebHdfsClient
path_cwd (omniauci.remotes.ssh_paramiko.ParamikoSSI	icient method), 110
aurioute), 141	a = b $a = a = a = b$ () ($a = a = d = a = b = c = b = c = b = c = b = c = b = c = b = c = b = c = b = c = b = c = b = c = c$
noth dirnomo()	path_normpath() (omniduct.remotes.ssh.SSHClient
<pre>path_dirname() (om-</pre>	<pre>path_normpath() (omniduct.remotes.ssh.SSHClient</pre>
<pre>path_dirname() (om- niduct.filesystems.base.FileSystemClient method) 92</pre>	<pre>path_normpath() (omniduct.remotes.ssh.SSHClient</pre>

<i>method</i>), 141		niduct.remotes.base.RemoteClient	method),
path_separator	(<i>om</i> -	121	
niduct.filesystems.base.FileSystemClient		<pre>port_forward_stop()</pre>	(om-
attribute), 91		niduct.remotes.ssh.SSHClient metho	<i>d</i>), 132
path_separator	(<i>om</i> -	<pre>port_forward_stop()</pre>	(om-
niduct.filesystems.local.LocalFsClient at- tribute), 102		niduct.remotes.ssh_paramiko.ParamikoSSHClient method), 142	
<pre>path_separator (omniduct.filesystems.s3.S3</pre>	Client	<pre>port_forward_stopall()</pre>	(om-
attribute), 109	,	niduct.remotes.base.RemoteClient	method),
path_separator	(<i>om</i> -	121	(
niduct.filesystems.webhafs.webHafsClient		port_torward_stopall()	(<i>om</i> -
attribute), 110	(niauct.remotes.ssn.SSHCtient metho	a), 152
niduct remotes base Periode Client attr	(Om-	poit_ioiwaid_stopaii()	ikoSSHClient
124	iduie),	method) 142	ukossiiCiieni
path separator (omniduct remotes ssh SSHClient prepare() (omniduct caches base Cache method) 149			
attribute). 132	enem	prepare () (omniduct.caches.filesvstem.File	SystemCache
path separator	(om-	<i>method</i>), 154	~,~~~~
niduct.remotes.ssh paramiko.ParamikoSSHClientprepare() (omniduct.databases.base.DatabaseClient			
attribute), 141		method), 23	
<pre>populate_namespace()</pre>	(<i>om</i> -	prepare() (omniduct.databases.druid.l	DruidClient
niduct.registry.DuctRegistry method), 157	7	method), 30	
port (omniduct.caches.filesystem.FileSystemCach	he at-	prepare() (omniduct.databases.hiveserver.	2.HiveServer2Client
tribute), 154		method), 42	
port (omniduct.databases.druid.DruidClient attra	ibute),	<pre>prepare() (omniduct.databases.neo4j.l</pre>	Veo4jClient
30 <i>method</i>), 52			
port (omniduct.databases.hiveserver2.HiveServer attribute), 41	2Client	prepare() (omniduct.databases.presto.F method), 62	restoClient
port (omniduct.databases.neo4j.Neo4jClient attra	ibute),	prepare() (omniduct.databases.pyspark.Py	SparkClient
52		method), 73	
port (omniduct.databases.presto.PrestoClient tribute), 62	at-	prepare() (omniduct.databases.sqlalchemy method), 83	y.SQLAlchemyClient
port (omniduct.databases.pyspark.PySparkClier	nt at-	<pre>prepare() (omniduct.duct.Duct method), 1</pre>	3
tribute), 73 prepare () (omniduct.filesystems.base.FileSystemClient			ystemClient
port (omniduct.databases.sqlalchemy.SQLAlchemyClient method), 96			
allribule), 83		prepare() (<i>omniauci.filesystems.local.Loc</i>	calFsClient
port (omniduct.duci.Duci diffibule), 14	at	meinou), 102	nt mathod)
tribute). 102	u-	109	u method),
port (omniduct.filesystems.s3.S3Client attribute),	109	prepare() (omniduct.filesystems.webhdfs.W	VebHdfsClient
port (omniduct.filesystems.webhdfs.WebHdfsClient at-		method), 117	
tribute), 116		prepare() (omniduct.remotes.base.Re	emoteClient
<pre>port (omniduct.remotes.ssh.SSHClient attribute),</pre>	<i>method</i>), 124		
port (omniduct.remotes.ssh_paramiko.ParamikoS	SHClier	<pre>ntprepare() (omniduct.remotes.ssh.SSHClied</pre>	nt method),
attribute), 141		132	
port_forward()	(<i>om</i> -	<pre>prepare() (omniduct.remotes.ssh_paramik</pre>	o.ParamikoSSHClient
niduct.remotes.base.RemoteClient me	thod),	<i>method</i>), 142	
120		prepare_smartcards()	(om-
port_forward() (omniduct.remotes.ssh.SSH method), 132	Client	niduct.remotes.base.RemoteClient 120	method),
port_forward() (om- prepare_smartcards() (om-			
niduct.remotes.ssh_paramiko.ParamikoSS	SHClier	nt niduct.remotes.ssh.SSHClient metho	<i>d</i>), 133
method), 142	,	prepare_smartcards()	(om-
port forward stop()	(<i>om</i> -	niduct.remotes.ssh_paramiko.Param	ukoSSHClient
method), 143 PrestoClient (class in omniduct.databases.presto), 59 PrestoClient.Type (class in omniduct.databases.presto), 60 prune () (omniduct.caches.base.Cache method), 149 prune() (omniduct.caches.filesystem.FileSystemCache method), 154 PySparkClient (class in omniduct.databases.pyspark), 69 PySparkClient.Type (class in omniduct.databases.pyspark), 70

Q

query	() (omniduct.databases.base.Datab	baseClient
	method), 17	
query(() (omniduct.databases.druid.D	ruidClient
	<i>method</i>), 31	
query(() (omniduct.databases.hiveserver2.Hi method) 42	veServer2Cli
auerv	(omniduct databases neo4i N	eo4iClient
query	method) 52	eo ijeneni
auery	(omniduct databases presto Pr	estoClient
query	<i>method</i>), 63	esioeneni
query (() (omniduct.databases.pyspark.PySp	oarkClient
	method), 73	
query	() (omniduct.databases.sqlalchemy.SQ	LAlchemyCli
	method), 84	2
query	<pre>from file()</pre>	(<i>om</i> -
	niduct.databases.base.DatabaseClien	et (
	method), 19	
querv	<pre>from file()</pre>	(om-
1 1-	niduct.databases.druid.DruidClient	method).
	31	,,,
auerv	from file()	(om-
1 1-	niduct.databases.hiveserver2.HiveSer	rver2Client
	method), 42	
auerv	<pre>from file()</pre>	(om-
1 1-	niduct.databases.neo4i.Neo4iClient	method).
	53	,,
auerv	<pre>from file()</pre>	(om-
1 1-	niduct.databases.presto.PrestoClient	method).
	63	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
auerv	<pre>from file()</pre>	(om-
1 1-	niduct.databases.pvspark.PvSparkCli	ent
	method). 74	
querv	from file()	(om-
-1	niduct.databases.salalchemy.SOLAlci	hemvClient
	method). 84	
auerv	<pre>from template()</pre>	(om-
1 1 -	niduct.databases.base.DatabaseClien	et (
	method). 21	
querv	from template()	(om-
1 - 1	niduct.databases.druid.DruidClient	method).

31 query from template() (omniduct.databases.hiveserver2.HiveServer2Client method), 43 query from template() (omniduct.databases.neo4j.Neo4jClient method), 53 query_from_template() (omniduct.databases.presto.PrestoClient method), 63 query_from_template() (omniduct.databases.pyspark.PySparkClient method), 74 query_from_template() (omniduct.databases.sqlalchemy.SQLAlchemyClient method), 84 query_to_table() (*om*niduct.databases.base.DatabaseClient method), 21 ient query_to_table() (omniduct.databases.druid.DruidClient method), 31 query_to_table() (omniduct.databases.hiveserver2.HiveServer2Client method), 43 query to table() (omniduct.databases.neo4j.Neo4jClient method), ient 53 query_to_table() (omniduct.databases.presto.PrestoClient method), 64 query_to_table() (omniduct.databases.pyspark.PySparkClient method), 74 query to table() (omniduct.databases.sqlalchemy.SQLAlchemyClient

R

method), 84

read_only(omniduct.filesystems.base.FileSystemClient attribute), 92 read_only (omniduct.filesystems.local.LocalFsClient attribute), 102 read_only (omniduct.filesystems.s3.S3Client attribute), 110 read_only (omniduct.filesystems.webhdfs.WebHdfsClient attribute), 117 (omniduct.remotes.ssh.SSHClient read_only attribute), 133 read only (omniduct.remotes.ssh paramiko.ParamikoSSHClient attribute). 143 reconnect() (omniduct.caches.filesystem.FileSystemCache method), 154

<pre>reconnect() (omniduct.databases.druid.DruidClient method) 32</pre>	110 remove() (omniduct filesystems webhdfs WebHdfsClient
reconnect () (omniduct.databases.hiveserver2.HiveServ	per2Client method), 117
<i>method</i>), 43	remove() (omniduct.remotes.base.RemoteClient
<pre>reconnect() (omniduct.databases.neo4j.Neo4jClient</pre>	method), 124
method), 53	<pre>remove() (omniduct.remotes.ssh.SSHClient method),</pre>
<pre>reconnect() (omniduct.databases.presto.PrestoClient</pre>	133
method), 64	remove() (omniduct.remotes.ssh_paramiko.ParamikoSSHClient
reconnect () (omniduct.databases.pyspark.PySparkClie method) 74	nt method), 143 reset () (omniduct caches filesystem FileSystemCache
reconnect () (omniduct databases salalchemy SOI Alch	emvClient method) 155
method) 85	rosot () (omniduct databases druid DruidClient
memora), 65	mathod) 32
reconnect () (omniduct.duct.Duct method), 15	memou), 52
method), 102	method), 44
reconnect() (<i>omniduct.filesystems.s3.S3Client</i>	reset() (omniduct.databases.neo4j.Neo4jClient
<i>method</i>), 110	method), 54
<pre>reconnect() (omniduct.filesystems.webhdfs.WebHdfsCl</pre>	ieneset() (omniduct.databases.presto.PrestoClient method), 65
reconnect() (omniduct.remotes.ssh.SSHClient	reset() (ominut.databases.pyspark.PySparkClient
method), 133	method), /5
method), 143	method), 85
<pre>register() (omniduct.registry.DuctRegistry method),</pre>	reset() (omniduct.duct.Duct method), 13
156	reset() (omniduct.filesystems.local.LocalFsClient
register_from_config() (om-	<i>method</i>), 103
niduct.registry.DuctRegistry method), 157	reset() (omniduct.filesystems.s3.S3Client method),
register_magics() (om-	110
niduct.databases.base.DatabaseClient	<pre>reset() (omniduct.filesystems.webhdfs.WebHdfsClient</pre>
method), 24	<i>method</i>), 117
register magics() (om-	reset() (omniduct.remotes.ssh.SSHClient method),
niduct.databases.druid.DruidClient method),	133
32	reset() (omniduct.remotes.ssh paramiko.ParamikoSSHClient
register magics() (om-	method). 143
niduct.databases.hiveserver2.HiveServer2Client	
method), 43	S
register magics() (om-	$C^{2}C^{1}$ i ant (along in ampiduat flaguatoms s^{2}) 104
niduct databases neo4i Neo4iClient method)	California Turno (alass in annidust flagustams s ²)
53	105
register_magics() (om-	schemas (<i>omniduct.databases.hiveserver2.HiveServer2Client</i>
niduct.databases.presto.PrestoClient method),	attribute), 44
64	schemas (omniduct.databases.presto.PrestoClient at-
register_magics() (om-	tribute), 65
niduct.databases.pyspark.PySparkClient method), 74	schemas (omniduct.databases.sqlalchemy.SQLAlchemyClient attribute) 85
register magics() (om-	annoure), 65
niduct databases salalchemy SOI AlchemyClient	session_properties (Om-
method), 85	tribute), 16
RemoteClient (class in omniduct.remotes.base), 119	session_properties (om-
<pre>remove() (omniduct.filesystems.base.FileSystemClient method), 94</pre>	niduct.databases.druid.DruidClient attribute),
remove() (omniduct, filesystems.local.LocalFsClient	session properties (om
method), 102	niduct databases hivesenver? HiveSenver? Client
remove() (omniduct.filesystems.s3.S3Client method),	attribute), 44

session_properties	(om-	niduct.databases.hiveserver2.HiveServer	2Client
54	nouie),	cluss memou), ++	(
	(statement_creanup()	(Om - 1)
session_properties	(<i>om</i> -	niauci.aatabases.neo4j.Neo4jClient	class
niduct.databases.presto.PrestoClient att	ribute),	method), 54	
65		<pre>statement_cleanup()</pre>	(om-
session_properties	(<i>om</i> -	niduct.databases.presto.PrestoClient	class
niduct.databases.pyspark.PySparkClien	t	method), 65	
attribute), 75		<pre>statement_cleanup()</pre>	(om-
session_properties	(om-	niduct.databases.pyspark.PySparkClient	
niduct.databases.salalchemv.SOLAlcher	nvClient	class method), 75	
attribute). 85		statement cleanup()	(om-
set () (omniduct caches base Cache method) 14	16	niduct databases salalchemy SOLAlchem	vClient
s = t () (omniduct caches filesystem FileSystem	nCache	class method) 86	yenem
method) 155	ncuche	cluss memou), 60	(
method), 155	Carl	statement_nash()	(<i>Om-</i>
set_metadata() (<i>omniduci.caches.base</i>	e.Cacne	niauct.aatabases.base.DatabaseClient	class
method), 146		method), 16	
set_metadata()	(<i>om</i> -	<pre>statement_hash()</pre>	(om-
niduct.caches.filesystem.FileSystemCach	he	niduct.databases.druid.DruidClient	class
<i>method</i>), 155		method), 33	
<pre>show_port_forwards()</pre>	(<i>om</i> -	<pre>statement_hash()</pre>	(<i>om</i> -
niduct.remotes.base.RemoteClient m	iethod),	niduct.databases.hiveserver2.HiveServer	2Client
121		class method), 44	
show port forwards()	(om-	statement hash()	(om-
niduct remotes ssh SSHClient method)	134	niduct databases neo4i Neo4iClient	class
show port forwards ()	(om-	method) 54	crubb
niduct remotes ssh paramiko Paramiko	(Om SSHClion	itstatement hash()	(om-
mathod) 1/3	SITCHEN	niduct databases presto Presto Client	olass
method, 145	Clima	mauci.aaiabases.presio.FresioCiteni	class
snowair () (omniauci, juesystems. base. Fuesyste	emClient	methoa), 65	1
method), 93		statement_hash()	(<i>om</i> -
showdir() (omniduct.filesystems.local.LocalF	sClient	niduct.databases.pyspark.PySparkClient	
<i>method</i>), 103		class method), 75	
<pre>showdir() (omniduct.filesystems.s3.S3Client m</pre>	iethod),	<pre>statement_hash()</pre>	(om-
110		niduct.databases.sqlalchemy.SQLAlchem	yClient
showdir() (omniduct.filesystems.webhdfs.WebH	HdfsClien	t class method), 86	
<i>method</i>), 117		<pre>stream() (omniduct.databases.base.Database</pre>	Client
showdir() (omniduct.remotes.ssh.SSHClient m	iethod),	method), 18	
134		<pre>stream() (omniduct.databases.druid.Druid</pre>	lClient
showdir() (omniduct.remotes.ssh paramiko.Pa	aramikoS.	SHClient method), 33	
method), 143		<pre>stream() (omniduct.databases.hiveserver2.Hive</pre>	Server2
SOLAlchemyClient (class in	om-	method), 44	
niduct databases salalchemy) 80	0.117	stream() (omniduct databases neo4i Neo4	Client
SOINIchemyClient Type (class in	om-	method) 55	Cucin
niduct databases salalchemy) 81	Om	stream() (omniduct databases presto Presto	Client
Couchi ant (alaggin anniduat remotes sel) 125		method) 65	Cueni
SSHCITERIC (class in omniduct.remotes.ssn), 12.) (memoa), 05	Clima
SSHClient.lype (class in omniauci.remoi	es.ssn),	stream() (omniauci.aatabases.pyspark.PySpark	Client
126	,	method), /6	
<pre>statement_cleanup()</pre>	(<i>om</i> -	stream()(<i>omniduct.databases.sqlalchemy.SQLA</i>	lichemy
niduct.databases.base.DatabaseClient	class	<i>method</i>), 86	
method), 17		<pre>stream_to_file()</pre>	(om-
<pre>statement_cleanup()</pre>	(<i>om</i> -	niduct.databases.base.DatabaseClient	
niduct.databases.druid.DruidClient	class	method), 18	
method), 32		<pre>stream_to_file()</pre>	(<i>om</i> -
<pre>statement_cleanup()</pre>	(om-	niduct.databases.druid.DruidClient me	ethod),

ct.aatabases.base.DatabaseChent	class
<i>od</i>), 16	
hash()	(<i>om</i> -
ct.databases.druid.DruidClient	class
<i>od</i>), 33	
hash()	(<i>om</i> -
ct.databases.hiveserver2.HiveServe	r2Client
method), 44	
hash()	(<i>om</i> -
ct.databases.neo4j.Neo4jClient	class
<i>od</i>), 54	
hash()	(<i>om</i> -
ct.databases.presto.PrestoClient	class
<i>od</i>), 65	
hash()	(om-
ct.databases.pyspark.PySparkClien	t
method), 75	
hash()	(om-
ct.databases.sqlalchemy.SQLAlchen	nyClient
method), 86	
(omniduct.databases.base.Databas	eClient
<i>od</i>), 18	
(omniduct.databases.druid.Drui	dClient
<i>od</i>), 33	
mniduct.databases.hiveserver2.Hive	eServer2Client
<i>od</i>), 44	
(omniduct.databases.neo4j.Neo4	4jClient
<i>od</i>), 55	
(omniduct.databases.presto.Prest	oClient
<i>od</i>), 65	
mniduct.databases.pyspark.PySpar	kClient
<i>od</i>), 76	
mniduct.databases.sqlalchemy.SQL	AlchemyClient
<i>od</i>), 86	
file()	(om-
ct.databases.base.DatabaseClient	-
<i>od</i>), 18	
file()	(om-
ct.databases.druid.DruidClient m	ethod),
	179

33

<pre>stream_to_file()</pre>	(<i>om</i> -
niduct.databases.hiveserver2.HiveSer	ver2Client
method), 45	
<pre>stream_to_file()</pre>	(<i>om</i> -
niduct.databases.neo4j.Neo4jClient	method),
55	
<pre>stream_to_file()</pre>	(<i>om</i> -
niduct.databases.presto.PrestoClient	method),
66	
<pre>stream_to_file()</pre>	(<i>om</i> -
niduct.databases.pyspark.PySparkClie	ent
method), 76	
<pre>stream_to_file()</pre>	(<i>om</i> -
niduct.databases.sqlalchemy.SQLAlch	nemyClient
method), 86	

Т

table_desc() (om- niduct.databases.base.DatabaseClient	
method), 22	
table_desc() (om-	
niduct.databases.druid.DruidClient method), 34	
table_desc() (om-	
niduct.databases.hiveserver2.HiveServer2Client method), 45	
table_desc() (om-	
niduct.databases.neo4j.Neo4jClient method), 55	
table_desc() (om-	
niduct.databases.presto.PrestoClient method), 66	
table_desc() (om-	
niduct.databases.pyspark.PySparkClient method), 76	
table_desc() (om-	
niduct.databases.sqlalchemy.SQLAlchemyClient method), 87	
table_drop() (om-	
niduct.databases.base.DatabaseClient method), 22	
table_drop() (<i>om</i> -	
niduct.databases.druid.DruidClient method), 34	
table_drop() (<i>om</i> -	
niduct.databases.hiveserver2.HiveServer2Client method), 45	
table_drop() (om-	
niduct.databases.neo4j.Neo4jClient method), 56	
table_drop() (<i>om</i> -	
niduct.databases.presto.PrestoClient method), 66	

niduct.databases.pyspark.PySparkClient
method), 77
table drop() (om-
niduct databases salalchemy SOLAlchemyClient
method) 87
table ovieta() (om
(Om-
niauct.aatabases.base.DatabaseCilent
method), 22
table_exists() (om-
niduct.databases.druid.DruidClient method),
34
table_exists() (om-
niduct.databases.hiveserver2.HiveServer2Client
method), 45
table exists() (om-
niduct databases neo/i Neo/iClient method)
maaci.aaiabases.neo4j.weo4jCiieni meinoa),
table_exists() (<i>Om</i> -
niduct.databases.presto.PrestoClient method),
66
table_exists() (om-
niduct.databases.pyspark.PySparkClient
method), 77
table exists() (om-
niduct databases salalchemy SOLAlchemyClient
method) 87
(am)
niauct.aatabases.base.DatabaseClient
method), 22
table_head() (<i>om</i> -
table_head() (om- niduct.databases.druid.DruidClient method),
table_head() (om- niduct.databases.druid.DruidClient method), 34
table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om-
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neodiNeodiClient method)</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om-</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 77</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.pyspark.PySparkClient method), 77 table_head() (om- niduct.databases.salalchemySQLAlchemyClient</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method),</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 77 table_head() (om- niduct.databases.sqlalchemy.SQLAlchemyClient method), 87 table_list() (om- niduct.databases.base.DatabaseClient</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.pyspark.PySparkClient method), 77 table_head() (om- niduct.databases.sqlalchemy.SQLAlchemyClient method), 87 table_list() (om- niduct.databases.base.DatabaseClient method), 21</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 77 table_head() (om- niduct.databases.sqlalchemy.SQLAlchemyClient method), 87 table_list() (om- niduct.databases.base.DatabaseClient method), 21 table_list() (om-</pre>
<pre>table_head() (om- niduct.databases.druid.DruidClient method), 34 table_head() (om- niduct.databases.hiveserver2.HiveServer2Client method), 46 table_head() (om- niduct.databases.neo4j.Neo4jClient method), 56 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PrestoClient method), 67 table_head() (om- niduct.databases.presto.PySparkClient method), 77 table_head() (om- niduct.databases.sqlalchemy.SQLAlchemyClient method), 87 table_list() (om- niduct.databases.base.DatabaseClient method), 21 table_list() (om- niduct.databases.druid.DruidClient method),</pre>

<pre>table_list() niduct.databases.hiveserver2.HiveServer2</pre>	(om- 2Client	t
table_list() niduct.databases.neo4j.Neo4jClient me	(om- thod),	t
table_list() niduct.databases.presto.PrestoClient me	(om- thod),	t
table_list() <i>niduct.databases.pyspark.PySparkClient</i> method) 77	(om-	t
<pre>table_list() niduct.databases.sqlalchemy.SQLAlchemy </pre>	(om- yClient	t
<pre>method), 88 table_partition_cols() niduct.databases.base.DatabaseClient</pre>	(om-	t
<pre>method), 22 table_partition_cols() niduct.databases.druid.DruidClient me 25</pre>	(om- thod),	t
table_partition_cols() <i>niduct.databases.hiveserver2.HiveServer2</i> method) 46	(om- 2Client	t
<pre>table_partition_cols() niduct.databases.neo4j.Neo4jClient me 56</pre>	(om- thod),	t
<pre>table_partition_cols() niduct.databases.presto.PrestoClient me 67</pre>	(om- thod),	t
<pre>table_partition_cols() niduct.databases.pyspark.PySparkClient method), 77</pre>	(<i>om</i> -	t
<pre>table_partition_cols() niduct.databases.sqlalchemy.SQLAlchemy method), 88</pre>	(om- yClient	t
table_props() niduct.databases.base.DatabaseClient method), 23	(<i>om</i> -	t
table_props() <i>niduct.databases.druid.DruidClient</i> me 35	(om- thod),	t
<pre>table_props() niduct.databases.hiveserver2.HiveServer2. method), 46</pre>	(om- 2Client	t
table_props() niduct.databases.neo4j.Neo4jClient me 57	(om- thod),	t
<pre>table_props() niduct.databases.presto.PrestoClient me 67</pre>	(om- thod),	t
<pre>table_props() niduct.databases.pyspark.PySparkClient</pre>	(<i>om</i> -	t

table_	props() niduct.databases.sqlalchemy.SQLAlchemy	(om- Client
templa	method), 88 te_add() niduct.databases.base.DatabaseClient	(<i>om</i> -
templa	<pre>method), 19 te_add() niduct.databases.druid.DruidClient met</pre>	(om- hod),
templa	35 te_add() niduct.databases.hiveserver2.HiveServer2	(om- Client
templa	method), 47 te_add() _niduct databases neo4i Neo4iClientmet	(om- hod)
templa	57 te_add()	(<i>om</i> -
templa	68 te_add()	hod), (om-
templa	niduct.databases.pyspark.PySparkClient method), 78	(om-
сещрта	niduct.databases.sqlalchemy.SQLAlchemy method), 88	Client
templa	te_get() niduct.databases.base.DatabaseClient method), 19	(<i>om</i> -
templa	te_get() niduct.databases.druid.DruidClient met 35	(om- hod),
templa	te_get() niduct.databases.hiveserver2.HiveServer2 method), 47	(om- Client
templa	te_get()	(<i>om</i> -
	niduct.databases.neo4j.Neo4jClient met 57	hod),
templa	te_get() niduct.databases.presto.PrestoClient met 68	(om- hod),
templa	te_get() niduct.databases.pyspark.PySparkClient method), 78	(<i>om</i> -
templa	te_get() niduct.databases.sqlalchemy.SQLAlchemy method), 89	(om- Client
templa	te_names <i>niduct.databases.base.DatabaseClient</i> <i>tribute</i>), 19	(om- at-
templa	te_names <i>niduct.databases.druid.DruidClient attriv</i> 36	(om- bute),
templa	te_names <i>niduct.databases.hiveserver2.HiveServer2</i> <i>attribute</i>), 47	(om- Client

method), 78

templa	te_names	(<i>om</i> -
	niduct.databases.neo4j.Neo4jClient attri 57	bute),
templa	te_names	(om-
_	niduct.databases.presto.PrestoClient attri 68	bute),
templa	te_names	(om-
-	niduct.databases.pyspark.PySparkClient attribute), 78	*
templa	te_names	(<i>om</i> -
	niduct.databases.sqlalchemy.SQLAlchemy attribute), 89	Client
templa	<pre>te_render() niduct.databases.base.DatabaseClient method), 20</pre>	(<i>om</i> -
templa	te render()	(om-
L	niduct.databases.druid.DruidClient met 36	thod),
templa	te_render()	(<i>om</i> -
	niduct.databases.hiveserver2.HiveServer2 method), 47	Client?
templa	te_render()	(om-
	niduct.databases.neo4j.Neo4jClient met 57	thod),
templa	te_render()	(om-
	niduct.databases.presto.PrestoClient met 68	thod),
templa	te_render()	(om-
	niduct.databases.pyspark.PySparkClient method), 78	
templa	te_render()	(<i>om</i> -
	niduct.databases.sqlalchemy.SQLAlchemy method), 89	Client
templa	te_variables()	(<i>om</i> -
	niduct.databases.base.DatabaseClient method), 19	
templa	te_variables()	(om-
	niduct.databases.druid.DruidClient met 36	thod),
templa	te_variables()	(om-
	niduct.databases.hiveserver2.HiveServer2 method), 48	Client?
templa	te_variables()	(<i>om</i> -
	niduct.databases.neo4j.Neo4jClient met 58	thod),
templa	te_variables()	(<i>om</i> -
	niduct.databases.presto.PrestoClient met 69	thod),
templa	te_variables()	(<i>om</i> -
	niduct. databases. pyspark. PySparkClient	
	method), 79	
templa	te_variables()	(<i>om</i> -
	niduct.databases.sqlalchemy.SQLAlchemy method), 89	Client

U

up sot () (ampiduct caches base Cache method) 147
unset () (ommunch.caches.ouse.cache memora), 147
unset() (omniduct.caches.filesystem.FileSystemCache
method), 155
unset_namespace() (<i>omniduct.caches.base.Cache</i>
method), 148
unset namespace() (om-
niauct.cacnes.filesystem.FileSystemCacne
<i>method</i>), 155
update_host_keys() (om-
niduct remotes ssh SSHClient method), 134
upload() (ampiduct flagsstams has FileSystamClient
up10a0() (Ommauci.juesystems.ouse.ruesystemctiem
method), 95
upload() (omniduct.filesystems.local.LocalFsClient
method), 103
(ompiduct filesystems s3 S3Client method)
upload()(omniduct.filesystems.webhdfs.WebHdfsClient
<i>method</i>), 118
upload() (omniduct.remotes.ssh.SSHClient_method).
134
10+
up10ad() (omniauci.remoies.ssn_paramiko.ParamikosshCileni
method), 143
username(<i>omniduct.caches.filesystem.FileSystemCache</i>
attribute), 155
usornomo (omniduct databases druid DruidClient at
tribute) 27
tribute), 57
username (<i>omniduct.databases.hiveserver2.HiveServer2Client</i>
attribute), 48
username (omniduct.databases.neo4j.Neo4jClient at-
tribute) 58
noncompany (omniduat databasas prasto Prasto Cliant at
username (ommunci.aunouses.presio.i resiochem ai-
tribute), 69
username (<i>omniduct.databases.pyspark.PySparkClient</i>
attribute), 79
username (omniduct databases salalchemy SOLAlchemyClient
attribute) 00
username (<i>omniduct.duct.Duct attribute</i>), 14
username (omniduct.filesystems.local.LocalFsClient
attribute), 103
username (omniduct filesystems s3 S3Client attribute)
111
username(<i>omniduct.filesystems.webhdfs.WebHdfsClient</i>
attribute), 118
username (omniduct.remotes.ssh.SSHClient attribute).
135
usorpamo (amniduct remotes sch. naramiko Daramiko SCUClient
attribute), 144
14/
VV
(omniduat flagustama baga FileSustamClient

walk()	(omniduct.filesystems.base.FileSystem)	lient
	method), 94	

walk() (omniduct.filesystems.local.LocalFsClient method), 103

- walk() (omniduct.filesystems.s3.S3Client method), 111
- walk() (omniduct.filesystems.webhdfs.WebHdfsClient method), 118
- walk() (omniduct.remotes.ssh.SSHClient method), 135
- WebHdfsClient (class in omniduct.filesystems.webhdfs), 111
- WebHdfsClient.Type (class in omniduct.filesystems.webhdfs), 112